

The following Safety Datasheet is provided by **Osmo**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:

Osmo Polyx Oil Rapid



according to 1907/2006/EC, Article 31

Printing date 11.02.2022 Version number 15.6 (replaces version 15.4) Revision: 11.02.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Polyx®-Oil Rapid Trade name:

Article number: 3232 Clear satin; 3240 White transparent; 3262 Clear matt

1.2 Relevant identified uses of the substance or mixture

and uses advised against No further relevant information available.

Application of the substance

/ the mixture Paint

Coating compound/ Surface coating/ paint

1.3 Details of the supplier of the safety data sheet

Osmo Holz und Color GmbH & Co. KG Manufacturer/Supplier:

> Affhüppen Esch 12 D-48231 Warendorf

Germany

Further information

obtainable from: Product safety department

> Tel.: +49 (0) 251 / 692 - 188 Fax: +49 (0) 251 / 692 - 462 e-mail: helmut.starp@osmo.de

1.4 Emergency telephone

number: emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory service in

German and English

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

2.2 Label elements Hazard pictograms

Additional information:

Signal word Warning

Hazard statements H226 Flammable liquid and vapour.

Precautionary statements P101 If medical advice is needed, have product container or label at hand.

> P102 Keep out of reach of children. P210 Keep away from heat. - No smoking. P262 Do not get in eyes, on skin, or on clothing.

P271 Use only outdoors or in a well-ventilated area.

P501 Dispose of contents/container in accordance with national regulations. 3240: EUH211 Warning! Hazardous respirable droplets may be formed when

sprayed. Do not breathe spray or mist.

EUH210 Safety data sheet available on request.

(Contd. on page 2)



Printing date 11.02.2022 Version number 15.6 (replaces version 15.4) Revision: 11.02.2022

Trade name: Polyx®-Oil Rapid

(Contd. of page 1)

2.3 Other hazards Observe the general safety regulations when handling chemicals.

Always wear a dust mask when sanding.

Warning:

Wash out any used cloth impregnated with this product immediately after use

or store in an airtight container (danger of self-ignition)

Must not be applied on the same spraying stand as lacquers or lacquer

corrosives that contain NC (nitrocellulose). Risk of self-ignition.

Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:				
EC number: 918-481-9	aliphatic hydrocarbons, C10-C13	30–50%		
	🗞 Asp. Tox. 1, H304, EUH066			
	aliphatic hydrocarbons, C9-C10	≥10-<20%		
	Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336; Aquatic Chronic 3, H412			
CAS: 34590-94-8	Dipropylene glycol monomethyl ether	<2.5%		
EINECS: 252-104-2	substance with a Community workplace exposure limit			
CAS: 13463-67-7	titanium dioxide - aerodynamic dia meter >10 μm	0-2.5%		
EINECS: 236-675-5				

Additional information: The content of Titanium dioxide varies according to the colour shade.

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter \leq 10 μ m.

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: Take affected persons out into the fresh air.

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact: Rinse opened eye for several minutes under running water. If symptoms

persist, consult a doctor.

After swallowing: If swallowed, seek medical advice immediately and show this container or

label.

(Contd. on page 3)



according to 1907/2006/EC, Article 31

Printing date 11.02.2022 Version number 15.6 (replaces version 15.4) Revision: 11.02.2022

Trade name: Polyx®-Oil Rapid

(Contd. of page 2)

Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and

delayed Headache Dizziness

4.3 Indication of any

immediate medical attention

and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing

CO2, sand, extinguishing powder. Do not use water. agents:

For safety reasons unsuitable

extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or

mixture Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters

Protective equipment: No special measures required.

Additional information Dispose of fire debris and contaminated fire fighting water in accordance with

official regulations.

Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and

emergency procedures Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

Wear protective clothing.

Keep away from ignition sources.

6.2 Environmental

Do not allow product to reach sewage system or any water course. precautions:

Inform respective authorities in case of seepage into water course or sewage

system.

6.3 Methods and material for

containment and cleaning up: Warm water and cleansing agent

Absorb with liquid-binding material (sand, diatomite, acid binders, universal

binders).

Dispose of the material collected according to regulations. Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

(Contd. on page 4)



according to 1907/2006/EC, Article 31

Printing date 11.02.2022 Version number 15.6 (replaces version 15.4) Revision: 11.02.2022

Trade name: Polyx®-Oil Rapid

(Contd. of page 3)

Do not flush with water or aqueous cleansing agents

6.4 Reference to other

sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe

handling Use only in well ventilated areas.

Keep away from heat and direct sunlight.

Keep receptacles tightly sealed. Prevent formation of aerosols.

Open and handle receptacle with care.

General protective and

hygienic measures: Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Store protective clothing separately.

Do not inhale gases / fumes / aerosols.

Information about fire - and

explosion protection: Keep ignition sources away - Do not smoke.

Protect against electrostatic charges. Keep respiratory protective device available.

Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by

storerooms and receptacles: Store only in the original receptacle.

Store in a cool location.

Information about storage in

one common storage facility: Not required.

Further information about

storage conditions: Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Storage class: 3

7.3 Specific end use(s) No further relevant information available.

(Contd. on page 5)



Revision: 11.02.2022

Printing date 11.02.2022 Version number 15.6 (replaces version 15.4)

Trade name: Polyx®-Oil Rapid

(Contd. of page 4)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

aliphatic hydrocarbons, C10-C13

WA Short-term value: 1200 mg/m³

CEFIC-HSPA

34590-94-8 Dipropylene glycol monomethyl ether

IOELV Long-term value: 308 mg/m³, 50 ppm

Skin

PNECs

34590-94-8 Dipropylene glycol monomethyl ether

PNEC sea water
PNEC fresh water
19 mg/l
19 mg/l
19 mg/l
4,168 mg/l
PNEC sewage treatment plant
PNEC fresh water
19 mg/l
70.2 mg/kg
PNEC STP
4,168 mg/l

PNEC STP 4,168 mg/l
PNEC Sediment marine water 190 mg/kg

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Appropriate engineering

controls No further data; see item 7.

Individual protection measures, such as personal protective equipment

General protective and

hygienic measures: Do not eat, drink, smoke or sniff while working.

Do not carry product impregnated cleaning cloths in trouser pockets.

Keep away from foodstuffs, beverages and feed.

Avoid contact with the eyes and skin.

Immediately remove all soiled and contaminated clothing

Store protective clothing separately.

Do not inhale gases / fumes / aerosols.

Respiratory protection: Use suitable respiratory protective device only when aerosol or mist is formed.

Use a properly fitted, air-purifying or air-fed repirator complying with an approved standard if a risk assessment indicates this is necessary. Half mask with round thread connection EN 148-1 (screw-on filter) and

combination filter A1 - P2 according to German DIN EN 14387.

Not necessary if room is well-ventilated.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective

device.

(Contd. on page 6)



Printing date 11.02.2022 Version number 15.6 (replaces version 15.4) Revision: 11.02.2022

Trade name: Polyx®-Oil Rapid

(Contd. of page 5)

Hand protection Protective gloves

The glove material has to be impermeable and resistant to the product/ the

substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates

of diffusion and the degradation

Material of gloves The selection of the suitable gloves does not only depend on the material, but

also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be

checked prior to the application.

Penetration time of glove

material The exact break trough time has to be found out by the manufacturer of the

protective gloves and has to be observed.

For the permanent contact gloves made of the following

materials are suitable: Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 16523-1:2015: Level 6).

As protection from splashes gloves made of the following

materials are suitable:Nitrile rubber, NBREye/face protectionTightly sealed gogglesBody protection:Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state Fluid

Colour: According to product specification

Odour: Mild

Melting point/freezing point: Undetermined.

Boiling point or initial boiling point and boiling

range > 144 °C

Lower and upper explosion limit

 Lower:
 0.7 Vol %

 Upper:
 6.0 Vol %

Flash point: 45-52 °C (DIN EN ISO 2719)

Auto-ignition temperature: Product is not selfigniting.

pH Not applicable

(Contd. on page 7)



Revision: 11.02.2022

Printing date 11.02.2022

Version number 15.6 (replaces version 15.4)

Trade name: Polyx®-Oil Rapid

(Contd. of page 6)

Viscosity:

Kinematic viscosity at 20 °C 25-45 s (DIN EN ISO 2431/4mm)

>21 mm²/s (40°C) (calculated)

Dynamic: Not determined.

Solubility

water: Not miscible or difficult to mix.

Vapour pressure at 20 °C: 10 hPa

Density and/or relative density

Density at 20 °C: 0.88-0.95 g/cm³ (DIN 51757)

9.2 Other information

Appearance:

Form: Fluid

Important information on protection of health and

environment, and on safety.

Ignition temperature: 240 °C

Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

Solvent content:

VOC (EC) < 500 g/l (VOC-max. Cat A/i (2010) = 500 g/l)

Information with regard to physical hazard classes

Explosives

Void

Flammable gases

Void

Aerosols

Void

Oxidising gases

Void

Gases under pressure

Void

Flammable liquids

Flammable liquid and vapour.

Flammable solids

Void

(Contd. on page 8)



Revision: 11.02.2022

Printing date 11.02.2022

Version number 15.6 (replaces version 15.4)

		(Contd. of page
Self-reactive substances	and mixtures	
	Void	
Pyrophoric liquids		
Pyrophoric solids	Void	
	Void	
Self-heating substances	and mixtures	
	Void	
Substances and mixture	s, which emit flammable	
gases in contact with wa	ter	
gases in contact with wa	ter	
gases in contact with wa	ter	
gases in contact with wa		
	V oid	
	Void	
Oxidising liquids		
Oxidising liquids Oxidising solids	Void	
Oxidising liquids Oxidising solids	Void Void	
Oxidising liquids Oxidising solids Organic peroxides	Void Void	
Oxidising liquids Oxidising solids Organic peroxides Corrosive to metals	Void Void Void Void	
Oxidising liquids Oxidising solids Organic peroxides	Void Void	

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

(Contd. on page 9)



Printing date 11.02.2022 Version number 15.6 (replaces version 15.4) Revision: 11.02.2022

Trade name: Polyx®-Oil Rapid

(Contd. of page 8)

10.2 Chemical stability Thermal decomposition /

conditions to be avoided: No decomposition if used according to specifications.

10.3 Possibility of hazardous

reactions Reacts with fabric soaked in the product (e.g. cleaning wool).

10.4 Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

10.5 Incompatible materials:

No further relevant information available.

10.6 Hazardous

decomposition products: Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

Additional information:

Warning:

Wash out any used cloth impregnated with this product immediately after use

or store in an airtight container (danger of self-ignition)

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50	LD/LC50 values relevant for classification:				
aliphatic l	aliphatic hydrocarbons, C10-C13				
Oral	LD50	>5,000 mg/kg (rat)			
Dermal	LD50	>5,000 mg/kg (rat)			
Inhalative	LC50 / 4h	>5 mg/l (rat)			
aliphatic l	nydrocarbo	ns, C9-C10			
Oral	LD50	>2,000 mg/kg (rat)			
Dermal	LD50	>2,000 mg/kg (rat)			
Inhalative	LC50 / 4h	>20 mg/l (rat)			
34590-94-	34590-94-8 Dipropylene glycol monomethyl ether				
Oral	LD50	>5,000 mg/kg (rat)			
Dermal	LD50	>19,020 mg/kg (rat)			
		13,000–14,000 mg/kg (rabbit)			
Inhalative	LC50 / 4h	1,667 mg/l (rat)			
	LC50 / 72h	0.76 mg/l (selenastrum capricornutum)			

Skin corrosion/irritation Based on available data, the classification criteria are not met. **Serious eye damage/irritation** Based on available data, the classification criteria are not met.

Respiratory or skin

sensitisationBased on available data, the classification criteria are not met.Germ cell mutagenicityBased on available data, the classification criteria are not met.CarcinogenicityBased on available data, the classification criteria are not met.Reproductive toxicityBased on available data, the classification criteria are not met.

(Contd. on page 10)



according to 1907/2006/EC, Article 31

Printing date 11.02.2022 Version number 15.6 (replaces version 15.4) Revision: 11.02.2022

Trade name: Polyx®-Oil Rapid

(Contd. of page 9)

STOT-single exposure Based on available data, the classification criteria are not met. STOT-repeated exposure Based on available data, the classification criteria are not met. Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic tox	Aquatic toxicity:				
aliphatic hydrocarbons, C10-C13					
EC50 / 48h	>1,000 mg/l (Daphnia magna)				
IC50 / 72h	>1,000 mg/l (algae)				
LC50 / 96h	>1,000 mg/l (fish)				
aliphatic hydrocarbons, C9-C10					
EC50 / 24h	<130 mg/l (Oncorhynchus mykiss (Regenbogenforelle))				
	>100 mg/l (selenastrum capricornutum)				
34590-94-8	Dipropylene glycol monomethyl ether				
EC50 / 48h	70.2 mg/l				
	1,919 mg/l (Daphnia magna)				
LC50 / 96h	5.3 mg/l (Oncorhynchus mykiss (Regenbogenforelle))				
LC50 / 48h	LC50 / 48h 10.2 mg/l (Oncorhynchus mykiss (Regenbogenforelle))				

12.2 Persistence and

degradability No further relevant information available.

12.3 Bioaccumulative

No further relevant information available. potential 12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment PBT: Not applicable. vPvB: Not applicable.

12.6 Endocrine disrupting

The product does not contain substances with endocrine disrupting properties. properties

12.7 Other adverse effects

Additional ecological information:

General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly

hazardous for water

(Contd. on page 11)



Printing date 11.02.2022 Version number 15.6 (replaces version 15.4) Revision: 11.02.2022

Trade name: Polyx®-Oil Rapid

(Contd. of page 10)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation Must not be disposed together with household garbage. Do not allow product

to reach sewage system.

European waste catalogue

08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

15 01 10* packaging containing residues of or contaminated by hazardous substances

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

14.1 UN number or ID number	
ADR, IMDG, IATA	UN1263
14.2 UN proper shipping name	
ADR	1263 PAINT
IMDG, IATA	PAINT
14.3 Transport hazard class(es)	
ADR	
Class	3 (F1) Flammable liquids.
Label	3
IMDG, IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group	
ADR, IMDG, IATA	III
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	30
EMS Number:	F-E, <u>S-E</u>
Stowage Category	A

(Contd. on page 12)



Printing date 11.02.2022 Version number 15.6 (replaces version 15.4) Revision: 11.02.2022

Trade name: Polyx®-Oil Rapid

(Contd. of page 11)

Transport/Additional information:

ADR

Limited quantities (LQ) 5L

Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

Transport category 3

Tunnel restriction code D/E

IMDG

Limited quantities (LQ) 5L

Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

UN 1263 PAINT, 3, III

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU Named dangerous

substances - ANNEX INone of the ingredients is listed.Seveso categoryP5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-

tier requirements 5,000 t

Qualifying quantity (tonnes) for the application of upper-

tier requirements 50,000 t

REGULATION (EC) No

1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

(Contd. on page 13)



according to 1907/2006/EC, Article 31

Printing date 11.02.2022 Version number 15.6 (replaces version 15.4) Revision: 11.02.2022

Trade name: Polyx®-Oil Rapid

(Contd. of page 12)

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

National regulations:

GISBAU-Code GISCODE: Ö60

VOC (EC) < 500 g/l (VOC-max. = 500 g/l (2010 A/i))

15.2 Chemical safety

assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Reasons for alterations Formal Changes

Relevant phrases H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Department issuing SDS: product safety department

Contact: Hr. Dr. Starp

Version number of previous

version: 15.4

Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route

(European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)
PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category

3

(Contd. on page 14)



Revision: 11.02.2022

Printing date 11.02.2022

Version number 15.6 (replaces version 15.4)

Trade name: Polyx®-Oil Rapid

(Contd. of page 13)

Sources Safety data sheets from raw material suppliers

ECHA Portal

ESIS: European chemical Substances Information System

ΕU