



**WOOD  
FINISHES  
DIRECT**



Finish. Finished.

The following Product Datasheet is provided by **Osmo**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:

[Osmo Polyx Oil Raw \(3044\)](#)



## POLYX<sup>®</sup>-OIL EFFECT RAW

The tried and trusted Polyx<sup>®</sup>-Oil without the permanent wet effect!



3044 Raw  
Transparent



### PRODUCT DESCRIPTION

Transparent coloured, satin wood finish that uniquely combines the advantages of natural oils and waxes in one product.

Osmo Polyx<sup>®</sup>-Oil Effect Raw is resistant to dirt, water and abrasion and smoothens the surface.

In comparison to conventional finishes, the use of plant ingredients creates a more evenly coloured and more harmonious appearance. Simple application without primer or intermediate sanding – this saves time and money.

Suitable for wood; water-repellent surface does not crack, peel, flake or blister. Resistant to wine, beer, cola, coffee, tea, fruit juice, milk and water according to DIN 68861-1A – no water spots. When dry, finish is safe for humans, animals and plants and is suitable for children's toys as per EN 71.3 (European norm) and is saliva-resistant and sweatproof according to DIN 53160 (German industrial norm).

### RECOMMENDED USE

Osmo Polyx<sup>®</sup>-Oil Effect Raw is suitable for the protection and nearly invisible finish of all light-coloured interior woods, such as wooden floors and furniture.

### INGREDIENTS

Based on natural plant oils and waxes (sunflower oil, soya oil, thistle oil, carnauba wax and candelilla wax), paraffin, titanium dioxide white pigment, siccatives (drying agents) and water-repellent additives. De-aromatized white spirit (benzene-free). This product fulfils EU regulations (2004/42/EC) according to the VOC content of max. 500 g/l (Cat. A/i (2010)).

Detailed declaration of ingredients available upon request.

### TECHNICAL DATA

Specific gravity: 0.94-0.96 g/cm<sup>3</sup>

Viscosity: >70s DIN EN ISO 2431/3 mm, thixotropic

Odour: faint/mild, after drying odourless

Flash point: >60°C acc. DIN EN ISO 2719

### STORAGE

Up to 5 years and longer if can is kept dry and closed tightly. If thickened by frost, store for 24-36 hours at room temperature before use.

### SURFACE PREPARATION

Wood surface must be clean, dry and frost-free (moisture content max. 18%).

Osmo Polyx<sup>®</sup>-Oil Effect Raw is ready to use, please do not thin. Stir well before use.

Clean old microporous stains thoroughly. Old paints and lacquers must be completely removed. As a general rule, wear a dust mask during sanding works. Fill small cracks, larger joints or holes in wood (with Osmo Wood Filler).

Sand wood surfaces carefully. Begin with coarse sandpaper – final sanding work for flooring P120-150, for furniture P180-240. Before oiling the surface, remove sanding dust with a broom or vacuum.

The finished surface is, among other things, influenced by the wood's natural characteristics. Therefore, a trial application is always required, especially for unfamiliar surfaces.

### METHODS OF APPLICATION

Apply thinly and evenly to the clean and dry wood along the wood grain with Osmo Natural Bristle Brush, Osmo Microfibre Roller or Osmo Floor Brush 150 mm, and spread well. Allow to dry for approx. 24 hours with good ventilation.

After drying, quickly apply a second coat also thinly.

When renovating an already oiled surface, one coat applied to the clean and dry surface is usually sufficient.



## CLEANING OF TOOLS

With Osmo Brush Cleaner (free of aromatic compounds).

## DRYING TIME

Approx. 24 hours (normal climatic conditions, 23 °C/50 % rel. humidity). Lower temperatures and/or higher air humidity can increase the drying time. Allow for good ventilation while drying. After 2-3 weeks, surface is completely hardened.

## COVERAGE

1 litre covers approx. 30 m<sup>2</sup> with one coat.

Product coverage depends significantly on the character of the wood. All information refers to smooth and planed/cut surfaces. Other surfaces may lead to reduced coverage.

## NOTE

Polyx®-Oil Effect Raw protects wood nearly invisibly. Applying the product too generously and insufficient ventilation lead to delays in drying time and the typical smell of oil.

Any brushstrokes can be removed with an unused dry Microfibre Roller within 30 minutes after applying.

The natural colour tone of wood is preserved – it does not enhance the tone of wood, no permanent wet effect.

On dark/reddish wood species, Polyx®-Oil Effect Raw is visible as slightly white chalky surface. A trial application is recommended. For extractive-rich hardwoods (e.g. Wenge, Merbau, Jatoba etc.), we recommend using Osmo Wood Wax Finish Clear Extra Thin. A trial application is recommended.

Caution: Apply max. one coat thinly to cabinet interiors and drawers with a cloth.

## CAUTION

Keep out of the reach of children. Avoid contact with eyes, skin or clothes. Contains 2-butanonoxime. May produce an allergic reaction. If medical advice is necessary please show the container or label. Use only outside or in well ventilated areas.

Dispose of product residuals and completely emptied containers according to the local official guidelines (AVV 08 01 11).

Caution: Wash out any cloth impregnated with this product immediately or store in an airtight container (Danger of self-ignition). The dried finish is classified as B2 (normal flammability) according to DIN 4102 regulations.

Safety data sheet upon request.

## DISPOSAL

Dispose of leftover product and completely emptied packaging according to local official guidelines (waste code number 08 01 11). Only completely emptied cans can be recycled.

## COLOUR TONES

3044 Raw Transparent

## CAN SIZES

0.75 L; 2.50 L; 25 L

The above mentioned information is provided to the best of our knowledge however without any liability.

Version 06/15