

The following Safety Datasheet is provided by Osmo

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit: Osmo Polyx Oil Raw (3044) Page 1/9



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.02.2015

Version number 2

Revision: 26.02.2015

1.1 Product identifier				
Trade name:	Osmo Polyx® Oil Effect			
Article number:	3041, 3044, 3092			
1.2 Relevant identified uses of substance or mixture and use				
advised against	No further relevant information available.			
Application of the substance /	' the			
mixture	Priming			
	Coating compound/ Surface coating/ paint			
1.3 Details of the supplier of the safety data sheet				
Manufacturer/Supplier:	Osmo Holz und Color GmbH & Co. KG			
	Affhüppen Esch 12			
	D-48231 Warendorf			
Further information obtainal	ıble			
from:	Product safety department			
	Phone: +49 (0) 251 / 692 - 188			
	Fax: +49 (0) 251 / 692 - 462			
	e-mail: helmut.starp@osmo.de			
1.4 Emergency telephone				
number:	emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory service in Germ and English			

SECTION 2: Hazards identification

Regulation (EC) No 1272/2008	The product is not classified according to the CLP regulation.
Classification according to	
Directive 67/548/EEC or Directi	ve
1999/45/EC	Not applicable.
Information concerning	
particular hazards for human ar	nd
environment:	The product does not have to be labelled due to the calculation procedure of the
	"General Classification guideline for preparations of the EU" in the latest valid versio
Classification system:	The classification is according to the latest editions of the EU-lists and extended by
	company and literature data.
2.2 Label elements	
Labelling according to Regulation	on and a second s
(EC) No 1272/2008	Void
Hazard pictograms	Void
Signal word	Void
Hazard statements	Void



Printing date 26.02.2015

Version number 2

Revision: 26.02.2015

Trade name: Osmo Polyx® Oil Effect (Contd. of page 1) If medical advice is needed, have product container or label at hand. **Precautionary statements** Keep out of reach of children. P271 Use only outdoors or in a well-ventilated area. P262 Do not get in eyes, on skin, or on clothing. P501 Dispose of contents/container in accordance with local/regional/national/ international regulations. Additional information: Observe the general safety regulations when handling chemicals. Always wear a dust mask when sanding. Contains 2-butanonoxime. May produce an allergic reaction. Information concerning particular hazards for human and environment: Warning: Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition) 2.3 Other hazards Results of PBT and vPvB assessment **PBT**: Not applicable. vPvB: Not applicable. **SECTION 3: Composition/information on ingredients** 3.2 Mixtures **Description:** Mixture of substances listed below with nonhazardous additions. **Dangerous components:**

2 unger ous components.			
CAS: 64742-48-9	aliphatic hydrocarbons, C10-C13	Xn R65	25-50%
EC number: 918-481-9		R66	
Index number: 649-327-00-6		🚯 Asp. Tox. 1, H304	
Reg.nr.: 01-2119457273-39			
Additional information:	For the wording of the listed risk phrases re-	efer to section 16.	

SECTION 4: First aid measures

General information:	Immediately remove any clothing soiled by the product.
	Take affected persons out into the fresh air.
After inhalation:	Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult
	doctor if symptoms persist.
	In case of unconsciousness place patient stably in side position for transportation.
After skin contact:	Immediately wash with water and soap and rinse thoroughly.
	If skin irritation continues, consult a doctor.
After eye contact:	Rinse opened eye for several minutes under running water. Then consult a doctor.
After swallowing:	If swallowed, seek medical advice immediately and show this container or label.
-	(Contd. on page 3)

GR

Page 3/9



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.02.2015

Version number 2

Revision: 26.02.2015

(Contd. of page 2)

Trade name: Osmo Polyx® Oil Effect

4.2 Most important symptoms andeffects, both acute and delayedDiszinessHeadache

4.3 Indication of any immediatemedical attention and specialtreatment neededNo further relev

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media	
Suitable extinguishing agents:	CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant
	foam.
For safety reasons unsuitable	
extinguishing agents:	Water with full jet
5.2 Special hazards arising from	
the substance or mixture	Formation of toxic gases is possible during heating or in case of fire.
5.3 Advice for firefighters	
Protective equipment:	Mouth respiratory protective device.
Additional information	Cool endangered receptacles with water spray.
	Dispose of fire debris and contaminated fire fighting water in accordance with official
	regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and	
emergency procedures	Ensure adequate ventilation
	Keep away from ignition sources.
6.2 Environmental precautions:	Inform respective authorities in case of seepage into water course or sewage system.
	Do not allow to enter sewers/ surface or ground water.
6.3 Methods and material for	
containment and cleaning up:	Warm water and cleansing agent
	Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).
6.4 Reference to other sections	See Section 7 for information on safe handling.
	See Section 8 for information on personal protection equipment.
	See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handlingKeep away from heat and direct sunlight.
Use only in well ventilated areas.
Keep receptacles tightly sealed.
Prevent formation of aerosols.

(Contd. on page 4)

GB

Page 4/9



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.02.2015

Version number 2

Revision: 26.02.2015

Trade name: Osmo Polyx® Oil Effect

		(Contd. of page 3)			
Information about fire - and					
explosion protection:	Keep ignition sources away - Do not smoke.				
7.2 Conditions for safe storage, i					
Storage:					
Requirements to be met by					
storerooms and receptacles:	Store only in the original receptacle.				
	Store in a cool location.				
Information about storage in on	e				
common storage facility:	Do not store together with alkalis (caustic solutions).				
	Do not store together with oxidising and acidic materials.				
Further information about					
storage conditions:	Store in cool, dry conditions in well sealed receptacles.				
	Keep container tightly sealed.				
7.3 Specific end use(s)	No further relevant information available.				
CECTION 9. Encoded and the later and the second state of the					
SECTION 8: Exposure controls/personal protection					
Additional information about					
<i>design of technical facilities:</i> No further data; see item 7.					
	· · · · · · · · · · · · · · · · · · ·				
8.1 Control parameters					
Ingredients with limit values that	t require monitoring at the workplace:				
64742-48-9 aliphatic hydrocarb	ons, C10-C13				
TWA (8 H) Long-term value: 1.000 mg/m ³ , 150 ppm ppm					
Source: UK SIA					
Additional information:	The lists valid during the making were used as basis.				
8.2 Exposure controls					
Personal protective equipment:					
General protective and hygienic					
measures:	Immediately remove all soiled and contaminated clothing				

Respiratory protection:Do not carry product impregnated cleaning cloths in trouser pockets.Not necessary if room is well-ventilated.

Nitrile rubber, NBR

Use suitable respiratory protective device only when aerosol or mist is formed. Short term filter device:

Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working.

Protection of hands:Filter A/P2Protection of hands:The glove material has to be impermeable and resistant to the product/ the substance/
the preparation.
To avoid skin problems reduce the wearing of gloves to the required minimum.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Printing date 26.02.2015

Version number 2

Revision: 26.02.2015

Trade name: Osmo Polyx® Oil Effect

(Contd. of page 4) Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed. For the permanent contact gloves made of the following materials are suitable: Nitrile rubber, NBR Recommended thickness of the material: ≥ 0.4 mm For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable: Nitrile rubber, NBR Eye protection: Goggles recommended during refilling **Body protection:** Protective work clothing

*

SECTION 9: Physical and chemical properties

General Information			
Appearance:			
Form:	Viscous		
Colour:	According to product specification		
Odour:	Mild		
Change in condition			
Melting point/Melting range:	Undetermined.		
Boiling point/Boiling range:	> 180 °C		
Flash point:	> 61 °C (DIN EN ISO 2719)		
Ignition temperature:	240 °C		
Self-igniting:	Product is not selfigniting.		
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures a possible.		
Explosion limits:			
Lower:	0.7 Vol %		
Upper:	6.0 Vol %		
Density at 20 °C:	0.90 - 0.95 g/cm ³ (DIN 51757)		
Solubility in / Miscibility with			
water:	Not miscible or difficult to mix.		
Viscosity:			
Kinematic at 20 °C:	25 - 38 s (DIN 53211/4 mm)		
	>21 mm²/s (40 °C)		



Printing date 26.02.2015

Version number 2

Revision: 26.02.2015

	(Contd. of pa
Solvent content:	
VOC (EC)	< 500 g/l (VOC-max. = 500 g/l (2010 A/i))
9.2 Other information	No further relevant information available.
SECTION 10: Stability and	d reactivity
10.1 Reactivity	
10.2 Chemical stability	
Thermal decomposition /	
conditions to be avoided:	No decomposition if used according to specifications.
10.3 Possibility of hazardous	
reactions	Reacts with fabric soaked in the product (e.g. cleaning wool).
10.4 Conditions to avoid	No further relevant information available.
10.5 Incompatible materials:	No further relevant information available.
10.6 Hazardous decomposition	
products:	Carbon monoxide and carbon dioxide
	Nitrogen oxides (NOx)
Additional information:	Warning:
	Wash out any used cloth impregnated with this product immediately after use or s
	in an airtight container (danger of self-ignition)
	in an anti-fit container (dunger er ben fenden)

Acute toxicity:

LD/LC50 values relevant for classification:

64742-48-9 aliphatic hydrocarbons, C10-C13		
Oral	LD50	> 5000 mg/kg (rat) (OECD 401)
Dermal	LD50	> 5000 mg/kg (rat) (OECD 402)
Inhalative	LC50 / 4h	> 5 mg/l (rat) (OECD 403)

96-29-7 2-butanonoxime

Oral	LD50	3700 mg/kg (rat)
Dermal	LD50	200-2000 mg/kg (rat)
Inhalative	LC50 / 4h	>10.5 mg/l (rat)

Primary ir	ritant effec	et:	
on the skir	<i>ı:</i>	At long or repeated contact with skin it may cause dermatitis due to the	degreasing
		effect of the solvent.	
on the eye.	:	No irritating effect.	
Sensitisati	on:	Sensitising effect by skin contact is possible by prolonged exposure.	

(Contd. on page 7)



Printing date 26.02.2015

Version number 2

Revision: 26.02.2015

	(Contd. of page
Additional toxicological	(conta. of page
information:	The product is not subject to classification according to the calculation method of t
	General EU Classification Guidelines for Preparations as issued in the latest version.
	When used and handled according to specifications, the product does not have a
	harmful effects to our experience and the information provided to us.
Sensitisation	Contains 2-butanonoxime. May produce an allergic reaction.
SECTION 12: Ecological in	nformation
12.1 Toxicity	
Aquatic toxicity:	
64742-48-9 aliphatic hydrocarb	
EC50 / 48h > 1000 mg/l (daphnia	a) (OECD 202)
EC50/72h > 1000 mg/l (algae) (OECD 201)
LC50 / 96h > 1000 mg/l (fish) (C	DECD 203)
96-29-7 2-butanonoxime	
EC50 / 48h 201 mg/l (daphnia)	
IC50 / 72h 11.8 mg/l (algae)	
LC50 / 96h >100 mg/l (fish)	
12.2 Persistence and degradabilit	ty No further relevant information available.
12.3 Bioaccumulative potential	No further relevant information available.
12.4 Mobility in soil	No further relevant information available.
Additional ecological information General notes:	
General notes:	Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous t water
	Do not allow product to reach ground water, water course or sewage system.
12.5 Results of PBT and vPvB as	
PBT:	Not applicable.
vPvB:	Not applicable.
12.6 Other adverse effects	No further relevant information available.
SECTION 13: Disposal con	osiderations
13.1 Waste treatment methods	
Recommendation	Smaller quantities can be disposed of with household waste.
European waste catalogue	
08 01 11 waste paint and varnish	containing organic solvents or other dangerous substances
15.01.10 packaging containing re	sidues of or contaminated by dangerous substances

(Contd. on page 8)

Page 8/9



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.02.2015

Version number 2

Revision: 26.02.2015

(Contd. of page 7)

Trade name: Osmo Polyx® Oil Effect

Uncleaned packaging: Recommendation:

Disposal must be made according to official regulations.

14.1 UN-Number		
ADR, ADN, IMDG, IATA	Void	
14.2 UN proper shipping name		
ADR, ADN, IMDG, IATA	Void	
14.3 Transport hazard class(es)		
ADR, ADN, IMDG, IATA		
Class	Void	
14.4 Packing group		
ADR, IMDG, IATA	Void	
14.5 Environmental hazards:		
Marine pollutant:	No	
14.6 Special precautions for user	Not applicable.	
14.7 Transport in bulk according to Anne	ex II of	
MARPOL73/78 and the IBC Code	Not applicable.	
Transport/Additional information:	Not dangerous according to the above specifications.	

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations:	
GISBAU-Code	GISCODE: Ö60
VOC (EC)	< 500 g/l (VOC-max. = 500 g/l (2010 A/i))
15.2 Chemical safety assessment:	A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H304 May be fatal if swallowed and enters airways.

R65 Harmful: may cause lung damage if swallowed.

(Contd. on page 9)

GB



Printing date 26.02.2015

Version number 2

Revision: 26.02.2015

Trade name: Osmo Polyx® Oil Effect

	R66 Repeated exposure may cause skin dryness or cracking.
Department issuing MSDS:	product safety department
Contact:	Hr. Dr. Starp
Contact: Abbreviations and acronyms:	ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreeme concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)
	VOC: Volatile Organic Compounds (USA, EU)
	LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent
	LD50. Lettal dose, 50 percent