



WOOD FINISHES DIRECT

The following Safety Datasheet is provided by **Osmo**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:
[Osmo Teak Oil Spray \(008\)](#)

Material Safety Data Sheets
 according to 1907/2006/EC, Article 31

Printing date 22.05.2018

Version number 14

Revision: 08.05.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: 007 Osmo Teak-Oil Spray, Clear

1.2 Relevant identified uses of the substance or mixture and uses advised against

Application of the substance / the mixture No further relevant information available.

Maintenance product
 Paint

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Osmo Holz und Color GmbH & Co. KG
 Affhüppen Esch 12
 D-48231 Warendorf

Further information obtainable from:

Product safety department
 Phone: +49 (0) 251 / 692 - 188
 Fax: +49 (0) 251 / 692 - 462
 e-mail: helmut.starp@osmo.de

1.4 Emergency telephone number:

emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory service in German and English

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

2.2 Label elements**Labelling according to Regulation**

(EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms

GHS02

Signal word

Danger

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P260 Do not breathe spray.
 P262 Do not get in eyes, on skin, or on clothing.

(Contd. on page 2)

Material Safety Data Sheets

according to 1907/2006/EC, Article 31

Printing date 22.05.2018

Version number 14

Revision: 08.05.2018

Trade name: 007 Osmo Teak-Oil Spray, Clear

(Contd. of page 1)

P271 Use only outdoors or in a well-ventilated area.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Additional information:

Observe the general safety regulations when handling chemicals.
Always wear a dust mask when sanding.

2.3 Other hazards**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures**Description:** Mixture of substances listed below with nonhazardous additions.**Dangerous components:**

EC number: 918-481-9 Index number: 649-327-00-6 Reg.nr.: 01-2119457273-39	aliphatic hydrocarbons, C10-C13 Asp. Tox. 1, H304	25-50%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0	butane Flam. Gas 1, H220; Acute Tox. 3, H331; Press. Gas (Comp.), H280	10-25%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5	propane Flam. Gas 1, H220; Press. Gas (Comp.), H280	2.5-10%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-01-8	isobutane Flam. Gas 1, H220; Acute Tox. 3, H331; Press. Gas (Comp.), H280	≤ 2.5%

Additional information:

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures**General information:**

Immediately remove any clothing soiled by the product.
Take affected persons out into the fresh air.

After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

After skin contact:

In case of unconsciousness place patient stably in side position for transportation.

After eye contact:

Immediately wash with water and soap and rinse thoroughly.

After swallowing:

Rinse opened eye for several minutes under running water. Then consult a doctor.

4.2 Most important symptoms and effects, both acute and delayed

If swallowed, seek medical advice immediately and show this container or label.

Headache

(Contd. on page 3)

Material Safety Data Sheets
 according to 1907/2006/EC, Article 31

Printing date 22.05.2018

Version number 14

Revision: 08.05.2018

Trade name: 007 Osmo Teak-Oil Spray, Clear

(Contd. of page 2)

4.3 Indication of any immediate medical attention and special treatment needed

Dizziness

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.
 Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters

Protective equipment: Mouth respiratory protective device.
Additional information: Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.
 Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation
 Wear protective equipment. Keep unprotected persons away.
 Keep away from ignition sources.

6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.
 Inform respective authorities in case of seepage into water course or sewage system.

6.3 Methods and material for containment and cleaning up:

Warm water and cleansing agent
 Ensure adequate ventilation.

6.4 Reference to other sections

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Keep away from heat and direct sunlight.
 Keep receptacles tightly sealed.
 Use only in well ventilated areas.
 Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

(Contd. on page 4)

Material Safety Data Sheets
 according to 1907/2006/EC, Article 31

Printing date 22.05.2018

Version number 14

Revision: 08.05.2018

Trade name: 007 Osmo Teak-Oil Spray, Clear

(Contd. of page 3)

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

7.2 Conditions for safe storage, including any incompatibilities**Storage:****Requirements to be met by****storerooms and receptacles:**

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

Information about storage in one common storage facility:

Do not store together with alkalis (caustic solutions).

Do not store together with oxidising and acidic materials.

Further information about storage conditions:

Store only outside or in explosion proof rooms.

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

7.3 Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

Additional information about**design of technical facilities:**

No further data; see item 7.

8.1 Control parameters**Ingredients with limit values that require monitoring at the workplace:****106-97-8 butane**

WEL	Short-term value: 1810 mg/m ³ , 750 ppm
	Long-term value: 1450 mg/m ³ , 600 ppm
	Carc (if more than 0.1% of buta-1.3-diene)

74-98-6 propane

AGW	Long-term value: 1800 mg/m ³ , 1000 ppm 4(II);DFG
-----	---

75-28-5 isobutane

OEL	Short-term value: 3800 mg/m ³ , 750 ppm
	Long-term value: 1900 mg/m ³ , 600 ppm
	EH 40/97

Additional information:

The lists valid during the making were used as basis.

(Contd. on page 5)

Material Safety Data Sheets
 according to 1907/2006/EC, Article 31

Printing date 22.05.2018

Version number 14

Revision: 08.05.2018

Trade name: 007 Osmo Teak-Oil Spray, Clear

(Contd. of page 4)

8.2 Exposure controls**Personal protective equipment:****General protective and hygienic measures:**

Do not inhale gases / fumes / aerosols.
 Immediately remove all soiled and contaminated clothing
 Keep away from foodstuffs, beverages and feed.
 Avoid contact with the eyes and skin.
 Do not eat, drink, smoke or sniff while working.
 Do not carry product impregnated cleaning cloths in trouser pockets.

Respiratory protection:

Not necessary if room is well-ventilated.
 In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
 Short term filter device:

Filter A/P2

Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
 Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Nitrile rubber, NBR

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact gloves made of the following materials are suitable:

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 6).

As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR

Eye protection:

Tightly sealed goggles

Body protection:

Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties**General Information****Appearance:****Form:** Aerosol**Colour:** Clear**Odour:** Characteristic

(Contd. on page 6)

Material Safety Data Sheets
 according to 1907/2006/EC, Article 31

Printing date 22.05.2018

Version number 14

Revision: 08.05.2018

Trade name: 007 Osmo Teak-Oil Spray, Clear

(Contd. of page 5)

Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	Not applicable, as aerosol.
Flash point:	Not applicable, as aerosol.
Ignition temperature:	240 °C
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits:	
Lower:	0.6 Vol %
Upper:	8.5 Vol %
Vapour pressure at 20 °C:	2.1 hPa
Density:	Not determined.
Solubility in / Miscibility with water:	
	Not miscible or difficult to mix.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity

No further relevant information available.

10.2 Chemical stability**Thermal decomposition / conditions to be avoided:**

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
 Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

10.3 Possibility of hazardous reactions

Forms explosive gas mixture with air.
 Reacts with fabric soaked in the product (e.g. cleaning wool).

10.4 Conditions to avoid

No further relevant information available.

10.5 Incompatible materials:

No further relevant information available.

10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide
 Nitrogen oxides (NO_x)

(Contd. on page 7)

Material Safety Data Sheets
 according to 1907/2006/EC, Article 31

Printing date 22.05.2018

Version number 14

Revision: 08.05.2018

Trade name: 007 Osmo Teak-Oil Spray, Clear

(Contd. of page 6)

Additional information:**Warning:**

Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition)

Must not be applied on the same spraying stand as lacquers or lacquer corrosives that contain NC (nitrocellulose). Risk of self-ignition.

SECTION 11: Toxicological information

11.1 Information on toxicological effects**Acute toxicity**

Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:**aliphatic hydrocarbons, C10-C13**

Oral	LD50	> 5000 mg/kg (rat) (OECD 401)
Dermal	LD50	> 5000 mg/kg (rat) (OECD 402)
Inhalative	LC50 / 4h	21 mg/l (rat) (OECD 403)

Primary irritant effect:**Skin corrosion/irritation**

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**Germ cell mutagenicity**

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity**Aquatic toxicity:****aliphatic hydrocarbons, C10-C13**

EC50 / 48h	> 1000 mg/l (daphnia) (OECD 202)
EC50/ 72h	> 1000 mg/l (algae) (OECD 201)
LC50 / 96h	> 1000 mg/l (fish) (OECD 203)
Biolog. Abbaubarkeit	(leicht abbaubar)

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

(Contd. on page 8)

Material Safety Data Sheets
according to 1907/2006/EC, Article 31

Printing date 22.05.2018

Version number 14

Revision: 08.05.2018

Trade name: 007 Osmo Teak-Oil Spray, Clear

(Contd. of page 7)

Additional ecological information:

General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue

08 01 11	waste paint and varnish containing organic solvents or other dangerous substances
16 05 05	gases in pressure containers other than those mentioned in 16 05 04
15 01 11	metallic packaging containing a dangerous solid porous matrix (for example asbestos), including empty pressure containers

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

Recommended cleansing agents: Solvent naphtha

SECTION 14: Transport information

14.1 UN-Number

ADR, IMDG, IATA UN1950

14.2 UN proper shipping name

ADR 1950 AEROSOLS

IMDG AEROSOLS

IATA AEROSOLS, flammable

14.3 Transport hazard class(es)**ADR**

Class 2 5F Gases.

Label 2.1

IMDG, IATA

Class 2.1

Label 2.1

(Contd. on page 9)

Material Safety Data Sheets
according to 1907/2006/EC, Article 31

Printing date 22.05.2018

Version number 14

Revision: 08.05.2018

Trade name: 007 Osmo Teak-Oil Spray, Clear

(Contd. of page 8)

14.4 Packing group ADR, IMDG, IATA	Void
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user Danger code (Kemler): EMS Number: Stowage Code Segregation Code	Warning: Gases. - F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code	1L Code: E0 Not permitted as Excepted Quantity 2 D
IMDG Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
UN "Model Regulation":	UN1950, AEROSOLS, 2.1

(Contd. on page 10)

Material Safety Data Sheets
according to 1907/2006/EC, Article 31

Printing date 22.05.2018

Version number 14

Revision: 08.05.2018

Trade name: 007 Osmo Teak-Oil Spray, Clear

(Contd. of page 9)

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

**Qualifying quantity (tonnes) for
the application of lower-tier
requirements** 150 t

**Qualifying quantity (tonnes) for
the application of upper-tier
requirements** 500 t

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H220 Extremely flammable gas.
H280 Contains gas under pressure; may explode if heated.
H304 May be fatal if swallowed and enters airways.
H331 Toxic if inhaled.

Department issuing SDS: product safety department

Contact: Hr. Dr. Starp

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Gas 1: Flammable gases – Category 1
Aerosol 1: Aerosols – Category 1
Press. Gas (Comp.): Gases under pressure – Compressed gas
Acute Tox. 3: Acute toxicity – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1

*** Data compared to the previous
version altered.**