



WOOD FINISHES DIRECT

The following Technical Datasheet is provided by **Polyvine**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:
[Polyvine Chalk Paint Waxer](#)

CHALK PAINT WAXER

DESCRIPTION

Combines the silky feel of wax with the durability of a varnish. Reminiscent of the traditional feel of lovingly preserved furniture. Retains the natural appearance of the paint, previously only obtainable by Master Craftsmen Interior, the perfect finish on: Chalk Paint Maker, Chalk Paint.

Available finishes Satin for depth and a soft sheen, dead flat for a completely shine free surface

APPLICATION

All surfaces must be clean and free from dust, dirt, oil and contamination. Ensure the product is well mixed but do not shake. Apply sparingly, brush out well using a good quality brush. Apply the first coat and allow to dry. Apply a second coat. On porous surfaces dilute the first coat 10% with water.

For increased durability and stain resistance first apply 2 coats of Wax Finish Varnish Satin followed by 1 coat of Wax Finish Varnish Dead Flat. This will result in a slightly brighter finish than using Wax Finish Varnish Dead Flat only.

caution Always apply to a test area before starting work. Appearance may vary according to the colour and type of paint and the number of coats. Do not apply over uncured paints.

COVERAGE

Approx. 15 sq. m per litre, 150 sq. ft per US qt

SHEEN LEVEL

Dead Flat & Satin

CONTAINERS

500ml, US pint,

DRYING TIME

15mins-1 hr, depending on temperature

RECOAT TIME

2hrs – 4hrs

CURING

Protect the finish from water and steam for 5 Days after application

CLEANING

Clean tools/equipment with warm soapy water, rinse well with clean water, allow to dry naturally.

STORAGE

Protect from extremes of temperature during storage and application.

CAUTION.

Always apply to a test area before starting work.

Appearance may vary according to the colour and type of paint and the number of coats.

Do not apply over oil based finishes

HEALTH SAFETY AND THE ENVIROMENT

Non-hazardous. Ensure good ventilation. Keep out of reach of children. Contact with eyes-wash immediately with warm water. Remove excess from tools and mixing vessels before washing in warm soapy water. Do not empty containers into drains or watercourses.

Date of Issue: January 2019

Further information may be obtained from:

Polyvine Limited, Vine House, Cheddar Business Park, Wedmore Road, Cheddar, BS27 3EB

Tel 01934 740305 • www.polyvine.com • email info@polyvine.co.uk