



WOOD FINISHES DIRECT

The following Product Datasheet is provided by **Polyvine**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:
[Polyvine Exterior Wood Varnish](#)

EXTERIOR WOOD VARNISH

A non-yellowing, quick-drying clear finish that protects against UV light and weather damage. This Waterproof and UV-resistant, it is suitable for exterior softwood and hardwood timber applications, offering long-term preservation.

KEY FEATURES AND BENEFITS

- ✓ Clear finish
- ✓ UV resistant
- ✓ Waterproof
- ✓ Resists blistering and cracking
- ✓ High solids
- ✓ Biocide boost
- ✓ Preserves the timber
- ✓ Food and child safe

APPLICATION INFORMATION

Application tools:	Brush, roller, spray
Coverage:	10-20 sqm per Litre
Drying:	30 minutes
Recoatable:	4 hours
Full cure:	5 days

AVAILABLE IN

Finishes:	Dead flat, satin
Sizes:	100ml, 500ml, 1L & 4L



Picture: Exterior Wood Varnish (satin)

ADDITIONAL INFORMATION

Always apply to a test area before starting work.
Appearance may vary according to the colour, type of surface, and the number of coats.

Coating life will be reduced on horizontal surfaces and where the coating is in contact with the ground or pooled water.

Dilute 10% with water to prime porous surfaces.

Do not apply when rain is imminent.

Do not shake the product.