



# WOOD FINISHES DIRECT

The following Technical Datasheet is provided by **Polyvine**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:  
[Polyvine Metallic Paint](#)

## METALLIC PAINT

Exterior Interior

### DESCRIPTION

The deep rich colours of Polyvine metallic paint give a sleek, luminous finish and dry to a polished lustre. Used by decorative artists worldwide, the shimmering richness of classic metals creates a luxurious finish for both inside and out. This unique blend of fine metallic lustre particles and hard lacquer has good brushing and spreading properties, giving an extra hard, high quality gloss finish. ideal to use on interior walls and plaster work picture frames and mirror surrounds interior - furniture and pottery exterior metalwork - gates, railings and door furniture unique qualities highly durable silky lustre finish water wash up water and heat resistant easy to apply water based retains metallic lustre for years does not discolour outside Available in Pale Gold, Bright Gold, Antique Gold, Copper, Pewter, Silver, Pearlescent.

### APPLICATION

preparation Ensure all surfaces are sound, clean, dry and free from rust and contamination. Previously painted: lightly abrade before application to provide a key. Ensure the product is thoroughly mixed. Try a small test area first. Apply 2-3 coats as required with a good quality brush. Roller and spray application. On porous surfaces dilute the first coat with 10% water.

**caution** Light reflection will accentuate brush marks and imperfections in the background. The covering ability of this paint will vary with the colour. It is essential to do a test area before application.

Use a similar base coat colour to greatly increase the covering power.

Ensure the product is well mixed.

Applying in high temperatures or direct sunlight will affect drying time. Do not apply when rain is imminent.

Protect from extremes of temperature

On bare wood lightly sand the first coat to remove grain raising.

Take care to eliminate brush/roller marks by over brushing. Brush marks will be highlighted by the metallic sheen.

Stippling the wet surface with a stippling brush will produce a hammered finish.

Spray application will ensure a smooth metallic surface.

### COVERAGE

Approx. 8 sq. m per litre 85 sq. ft per US qt

### SHEEN LEVEL

Semi gloss

### No OF COATS

2/ 3 coats

### DRYING TIME

15mins-1 hr, depending on temperature

### RECOAT TIME

2hrs – 4hrs

### CURING

5-7 days. Before placing heavy objects on surface.

### CONTAINERS

50ml, 250ml, 500ml, 1L, 2.5L. US 8.8oz, US Quart, US 87.9oz.

### CLEANING

Clean tools/equipment with warm soapy water, rinse well with clean water, and allow to dry naturally.

Further information may be obtained from:

Polyvine Limited, Vine House, Cheddar Business Park, Wedmore Road, Cheddar, BS27 3EB

Tel 01934 740305 • [www.polyvine.com](http://www.polyvine.com) • email [info@polyvine.co.uk](mailto:info@polyvine.co.uk)

## **STORAGE**

Protect from extremes of temperature during storage and application.

## **HEALTH SAFETY AND THE ENVIROMENT**

Non-hazardous. Ensure good ventilation. Keep out of reach of children. Contact with eyes-wash immediately with warm water. Remove excess from tools and mixing vessels before washing in warm soapy water. Do not empty containers into drains or watercourses.

The information supplied herein is accurate to the best of our knowledge. Since conditions and methods are beyond our control, no warranty is expressed or implied. You are advised to assess the suitability of the product on a test area before application

Date of issue: January 2019

Further information may be obtained from:

Polyvine Limited, Vine House, Cheddar Business Park, Wedmore Road, Cheddar, BS27 3EB

Tel 01934 740305 • [www.polyvine.com](http://www.polyvine.com) • email [info@polyvine.co.uk](mailto:info@polyvine.co.uk)