



WOOD FINISHES DIRECT

The following Product Datasheet is provided by **Polyvine**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:
[Polyvine Metallic Shimmer](#)

METALLIC SHIMMER

Exterior Interior

DESCRIPTION

Polyvine unique colourable metallic shimmer gives a sleek, luminous finish that lends a shimmering richness to classic decor and introduces a timeless luxury to a wide range of architectural elements. This fast drying metallic shimmer is frequently specified for use in hotels, bars and restaurants, theatres, churches, museums, civic buildings and famous country houses - anywhere the highest level of metallic decorative effect is required. Now you can create the metallic colour of your choice or mix one to match your colour scheme, using metallic shimmer and our acrylic colourants. Used direct from the tin, metallic shimmer creates a shimmering pearl finish.

ideal to use on • interior walls • plaster work • picture frames • mirror surrounds • furniture • pottery • railings • exterior metalwork • architectural ironmongery

unique qualities • highly durable • doesn't need protection • silky lustre finish • water and heat resistant • interior/exterior • water based • doesn't tarnish, ever

APPLICATION

Pour your 500ml of metallic shimmer into a mixing vessel and add the whole bottle 50g of Polyvine acrylic colourant in the colour that you have chosen. Ensure the product is thoroughly mixed. Try a small test area first. Apply 2-3 coats as required with a good quality brush. You can use a similar base coat colour to greatly increase the covering power. To create paler colours or tints just add smaller amounts of colourant and for darker tints, use more colourant.

preparation Ensure all surfaces are sound, clean, dry and free from rust and contamination. Previously painted: lightly abrade before application to provide a key. Ensure the product is thoroughly mixed. Try a small test area first. Apply 2-3 coats as required with a good quality brush. Roller and spray application. On porous surfaces dilute the first coat with 10% water.

caution Light reflection will accentuate brush marks and imperfections in the background. The covering ability of this paint will vary with the colour. It is essential to do a test area before application.

Use a similar base coat colour to greatly increase the covering power.

Ensure the product is well mixed.

Applying in high temperatures or direct sunlight will affect drying time. Do not apply when rain is imminent.

Protect from extremes of temperature

On bare wood lightly sand the first coat to remove grain raising.

Take care to eliminate brush/roller marks by over brushing. Brush marks will be highlighted by the metallic sheen.

Stippling the wet surface with a stippling brush will produce a hammered finish.

Spray application will ensure a smooth metallic surface.

COVERAGE

Approx. 10 sq. m per litre 100sq. ft per US qt

SHEEN LEVEL

Semi gloss

No OF COATS

2/ 3 coats

DRYING TIME

15mins-1 hr, depending on temperature

RECOAT TIME

2hrs – 4hrs

CURING

5-7 days. Before placing heavy objects on surface.

Further information may be obtained from:

Polyvine Limited, Vine House, Cheddar Business Park, Wedmore Road, Cheddar, BS27 3EB

Tel 01934 740305 • www.polyvine.com • email info@polyvine.co.uk

CONTAINERS

500ml, 1L, 2.5L. US 8.8oz, US Quart, US 87.9oz.

CLEANING

Clean tools/equipment with warm soapy water, rinse well with clean water, and allow to dry naturally.

STORAGE

Protect from extremes of temperature during storage and application.

The information supplied herein is accurate to the best of our knowledge. Since conditions and methods are beyond our control, no warranty is expressed or implied. You are advised to assess the suitability of the product on a test area before application

Date of issue: January 2019

Further information may be obtained from:

Polyvine Limited, Vine House, Cheddar Business Park, Wedmore Road, Cheddar, BS27 3EB

Tel 01934 740305 • www.polyvine.com • email info@polyvine.co.uk