



WOOD FINISHES DIRECT

The following Technical Datasheet is provided by **Polyvine**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:
[Polyvine Wax Finish Varnish - Coloured](#)

WAX FINISH VARNISH

DESCRIPTION

Combines the silky feel of wax with the durability of a varnish. Reminiscent of the traditional feel of lovingly preserved furniture. Retains the natural appearance of the wood. The colour transforms the wood, producing subtle even shades, previously only obtainable by Master Craftsmen

Interior, the perfect finish on: Wood and MDF, new wood furniture, bookshelves, fire surrounds, kitchen cabinets, staircases, doors

Available finishes Satin for depth and a soft sheen, dead flat for a completely shine free surface, coloured satin to transform wood with subtle, even shades.

For a completely non reflective finish, apply clear dead flat over coloured satin.

APPLICATION

All surfaces must be clean and free from dust, dirt, oil and contamination. Ensure the product is well mixed but do not shake. Apply sparingly, brush out well using a good quality brush. Apply the first coat and allow to dry. Apply a second coat. On new wood and porous surfaces dilute the first coat 10% with water. Lightly sand wood in between applications to remove any raising of the grain that may have occurred. For a high level of durability and stain resistance, apply two coats of clear satin and one coat of clear dead flat.

CLEAR apply a second coat.

COLOURS For a deeper colour apply a second coat. If the colour is correct on the first coat, the finish and durability can be greatly enhanced by applying the second coat in clear.

For dead flat coloured Wax Finish Varnish apply colour as above and finish with dead flat clear.

For increased durability and stain resistance first apply 2 coats of Wax Finish Varnish followed by 1 coats of Wax Finish Varnish Dead Flat. This will result in a slightly brighter finish than using Wax Finish Varnish Dead Flat only.

caution Always apply to a test area before starting work. Appearance may vary according to the colour and type of wood and the number of coats. Do not apply over uncured oil paints.

COVERAGE

Approx. 15 sq. m per litre, 150 sq. ft per US qt

SHEEN LEVEL

Dead Flat & Satin

CONTAINERS

500ml, 1L, 4L. US pint, US Quart, US Gal

DRYING TIME

15mins-1 hr, depending on temperature

RECOAT TIME

2hrs – 4hrs

CURING

Protect the finish from water and steam for 5 Days after application

CLEANING

Clean tools/equipment with warm soapy water, rinse well with clean water, allow to dry naturally.

STORAGE

Protect from extremes of temperature during storage and application.

CAUTION.

Always apply to a test area before starting work.

Appearance may vary according to the colour and type of wood and the number of coats.

Do not apply over oil based finishes

Further information may be obtained from:

Polyvine Limited, Vine House, Cheddar Business Park, Wedmore Road, Cheddar, BS27 3EB

Tel 01934 740305 • www.polyvine.com • email info@polyvine.co.uk

HEALTH SAFETY AND THE ENVIROMENT

Non-hazardous. Ensure good ventilation. Keep out of reach of children. Contact with eyes-wash immediately with warm water. Remove excess from tools and mixing vessels before washing in warm soapy water. Do not empty containers into drains or watercourses.

The information supplied herein is accurate to the best of our knowledge. Since conditions and methods are beyond our control, no warranty is expressed or implied. You are advised to assess the suitability of the product on a test area before application

Date of issue: January 2019

Further information may be obtained from:

Polyvine Limited, Vine House, Cheddar Business Park, Wedmore Road, Cheddar, BS27 3EB

Tel 01934 740305 • www.polyvine.com • email info@polyvine.co.uk