



WOOD FINISHES DIRECT

The following Technical Datasheet is provided by **Prestonett**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:

[Prestonett Ready Mixed Flexible Crack Repair Filler](#)

INT/EXT READY MIXED FLEXIBLE CRACK REPAIR FILLER



GENERAL INFORMATION

Description

Ready mixed flexible crack repair filler

Intended use

Interior/exterior

- Repairs to reoccurring cracks due to structural movement



PRODUCT ADVANTAGES

- + Highly flexible
- + Excellent adhesion to substrates
- + Fibreglass reinforced for moving cracks
- + Waterproof
- + No fibre tape or fabric required
- + White

USE

DILUTION

Ready mixed

APPLICATION

Conditions

Do not apply at temperatures of below +5°C or above +35°C, or at a relative humidity of above 80% H.R.

Equipment

Blade, smoothing trowel, filling knife.

Operational mode

Clean out crack, apply a bead down the length of the crack and then smooth with a spatula extending past the edge of the crack and ensure no air pockets are left. Allow to set for 6-8 hours before applying a second coat if required.

Equipment cleaning

With water before completely dry.

Do not throw away into drains, dispose of this material and its container to an approved disposal contractor or taken to municipal collection point. Do not dispose into the environment.

RECOMMANDATIONS

This product is **not sandable**, smooth over with a wet spatula before completely dry to achieve a smooth surface.

APPLICATION THICKNESS

3 mm

AVERAGE CONSUMPTION

83 ml/m²/mm thickness

SUBSTRATES

Concrete, cellular concrete, gypsum board, cement, concrete block, brick, plaster, ceramic tiles, old painted substrates.

Substrates must be hard, cohesive, clean, sound and dry according to the local standards.

OVERCOAT

Primer, interior conventional paint, light-weight wall coverings.

INT/EXT READY MIXED FLEXIBLE CRACK REPAIR FILLER

TECHNICAL DATA



COMPONANTS Based on acrylic copolymers.

DENSITY 1.2 ± 0.1

pH 8 ± 0.5

COLOUR White

WORKING TIME AT 20°C Unlimited

WAITING TIME BEFORE OVERCOATING 2 – 24 hours

CLASSIFICATION NFT 36 005 famille IV class 4b

V.O.C < 10 g/l (Ready mixed)

HEALTH AND SAFETY



Use in a well-ventilated place. Avoid direct contact with skin and eyes. Do not breathe dust.

In case of prolonged contact, it is recommended to wear suitable gloves. Safety data sheet available on www.beissier.eu or www.quickfds.com

PACKAGING 750 ml bucket – 200 ml tube

STORAGE 12 months from date of manufacture, in unopened original packaging, protected from frost, heat (max. +30°C), sun and moisture. Close well after use. Store in original packaging.

This data sheet supersedes and replaces any prior sheet relating to the same product.

Date of issue : April 2017

The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information is no substitute for a description pertaining specifically to the type and condition of the substrate concerned. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that updated edition of this sheet has not been issued.