

The following Safety Datasheet is provided by Repair Care

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit: Repair Care BIO FLEX COOL



# BIO FLEX<sup>™</sup> COOL A-component Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2016/1179 Date of issue: 04/07/2019 Version: 1.0

<b>SECTION 1: Iden</b>	tification of the subs	stance/mixture an	d of the comp	oany/undertaking	
1.1. Product ide					
Product form		: Mixture			
Product name	oduct name : BIO FLEX™ COOL A-component				
1.2. Relevant ide	entified uses of the subst	ance or mixture and u	ises advised aga	inst	
1.2.1. Relevant ide	entified uses				
Main use category		: Industrial use, Prof	essional use		
Use of the substance	Use of the substance/mixture : Elastic repair compound Product only to be used in combination with component B.				
1.2.2. Uses advise	-				
No additional informati					
1.3. Details of th Repair Care Internati	e supplier of the safety d	ata sheet			
	Nederland 5 - F + 31(0) 416 652024 <u>1</u> - <u>www.repair-care.com</u>				
1.4. Emergency	telephone number				
Country	Official advisory body	Address		Emergency number	Remark
United Kingdom	National Poisons Informati Service (Belfast Centre) Royal Victoria Hospital	Grosvenor Road BT12 6BA Belfast		0344 892 0111	Only for the purpose of informing medical personnel in cases of acute intoxications
SECTION 2: Haza	ards identification				
	on of the substance or mi	xture			
	ing to Regulation (EC) No		h its amondmon	Population (EU) 2016/	1170
Skin corrosion/irritatio		315	in its amenument		1113
	eye irritation, Category H				
2	, , , , , , , , , , , , , , , , , , , ,	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,			
	tegory 1 H	317			
Skin sensitisation, Ca					
Skin sensitisation, Ca Hazardous to the aqu Chronic Hazard, Cate	uatic environment — H4	411			

Circle of (CLD)		
Signal word (CLP)	: Warning	
Hazardous ingredients	<ul> <li>reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular w ≤ 700); 2-(chloromethyl)oxirane; Formaldehyde; Phenol; oxirane, mono[(C12-14- alkyloxy)methyl] derivs.; Cashew, nutshell liq.</li> </ul>	eight
Hazard statements (CLP)	<ul> <li>H315 - Causes skin irritation.</li> <li>H317 - May cause an allergic skin reaction.</li> <li>H319 - Causes serious eye irritation.</li> <li>H411 - Toxic to aquatic life with long lasting effects.</li> </ul>	
Precautionary statements (CLP)	<ul> <li>P261 - Avoid breathing vapours, mist, spray.</li> <li>P273 - Avoid release to the environment.</li> <li>P280 - Wear eye protection, protective gloves, protective clothing.</li> <li>P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</li> </ul>	е
	EN (English)	1/9

GHS09

GHS07

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2016/1179

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

> ( 5 =<C < 100) Skin Irrit. 2, H315 ( 5 =<C < 100) Eye Irrit. 2, H319

#### 2.3. Other hazards

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

### SECTION 3: Composition/information on ingredients

3.1. Substances

### Not applicable

#### 3.2. Mixtures

Name	Product identifier Conc. (% w/v		Classification according to Regulation (EC) No. 1272/2008 [CLP] with its amendment Regulation (EU) 2016/1179
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	(CAS-No.) 25068-38-6 (EC-No.) 500-033-5 (EC Index-No.) 603-074-00-8 (REACH-no) 01-2119456619-26	<50	Eye Irrit. 2, H319 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	(CAS-No.) 68609-97-2 (EC-No.) 271-846-8 (EC Index-No.) 603-103-00-4 (REACH-no) 01-2119485289-22	<25	Skin Irrit. 2, H315 Skin Sens. 1, H317
2-(chloromethyl)oxirane; Formaldehyde; Phenol	(CAS-No.) 28064-14-4 (EC-No.) 608-164-0	<25	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Cashew, nutshell liq.	(CAS-No.) 8007-24-7 (EC-No.) 232-355-4 (REACH-no) 01-2120038044-68	<2	Acute Tox. 4 (Dermal), H312 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412
Specific concentration limits: Name	Product identifier	Specific co	ncentration limits

(CAS-No.) 25068-38-6

(EC-No.) 500-033-5 (EC Index-No.) 603-074-00-8 (REACH-no) 01-2119456619-26

Full text of H-phrases: see section 16

(number average molecular weight ≤ 700)

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin

SECTION 4: First aid measures	
4.1. Description of first aid measures	
First-aid measures general	: Never give anything by mouth to an unconscious person. If medical advice is needed, have product container or label at hand. Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention i you feel unwell.
First-aid measures after skin contact	: Remove contaminated clothes. Wash skin with mild soap and water. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attentior
First-aid measures after ingestion	: Rinse mouth. Do not induce vomiting without medical advice. Get medical advice/attention if you feel unwell.
4.2. Most important symptoms and effective states and effective symptometry and effective symplex and effective	ffects, both acute and delayed
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.
4.3. Indication of any immediate med	ical attention and special treatment needed
Treat symptomatically.	
SECTION 5: Firefighting measures	\$
5.1. Extinguishing media	
Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.

# Safety Data Sheet

Unsuitable extinguishing media	: Do not use a heavy water stream.
5.2. Special hazards arising from the sub	stance or mixture
Fire hazard	: Presents no particular fire or explosion hazard.
Hazardous decomposition products in case of fire	: Carbon oxides (CO, CO2).
3. Advice for firefighters	
Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.
SECTION 6: Accidental release meas	ures
5.1. Personal precautions, protective equ	uipment and emergency procedures
6.1.1. For non-emergency personnel	
Emergency procedures	: Evacuate unnecessary personnel. Avoid contact with skin and eyes. Avoid breathing vapours mist, spray.
.1.2. For emergency responders	
Protective equipment	: Equip cleanup crew with proper protection. For further information refer to section 8: "Exposu controls/personal protection".
Emergency procedures	: Ventilate area.
.2. Environmental precautions	
o not allow to enter drains or water courses.	
.3. Methods and material for containme	nt and cleaning up
For containment	: Collect spillage.
Methods for cleaning up	: Take up liquid spill into absorbent material. Sweep or shovel spills into appropriate container disposal.
Other information	: Dispose of materials or solid residues at an authorized site.
6.4. Reference to other sections	
For further information refer to section 8: "Exposu	re controls/personal protection". Concerning disposal elimination after cleaning, see section 13.
SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Precautions for safe handling	: Concerning personal protective equipment to use, see section 8. Provide good ventilation in process area to prevent formation of vapour. Avoid contact with skin and eyes. Wear persona protective equipment. Avoid breathing vapours, mist, spray.
Handling temperature	: 5 - 50 °C
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Wash contaminated clothing before reuse. Contaminated work clothing should not b allowed out of the workplace.
2.2. Conditions for safe storage, includin	g any incompatibilities
Storage conditions	: Keep only in the original container in a cool well ventilated place. Keep container closed when not in use.
Incompatible products	: Oxidizing agents. Strong acids. Alkalines.
Storage temperature	: 20 °C (± 10°C)
Heat and ignition sources	: Keep away from heat and direct sunlight.
7.3. Specific end use(s)	
No additional information available.	
SECTION 8: Exposure controls/perso	nal protection
3.1. Control parameters	

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2016/1179

#### **Control parameters** 8.1.

No additional information available.

#### 8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

### Personal protective equipment:

Safety glasses. Gloves. protective clothing.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2016/1179

#### Hand protection:

Wear suitable gloves resistant to chemical penetration. Chemical resistant gloves (according to European standard NF EN 374 or equivalent).

Туре	Material	Permeation	Thickness (mm)	Penetration	Standard
Gloves	Nitrile rubber (NBR), Polyvinylchloride (PVC)	6 (> 480 minutes)	≥0.11		EN 374

### Eye protection:

Safety glasses. DIN EN 166

Туре	Use	Characterizations	Standard
Safety goggles	Droplet	With side shields	EN 166

#### Skin and body protection:

Wear suitable protective clothing. CEN : EN 340; EN 369; EN 465

#### Respiratory protection:

No special respiratory protection equipment is recommended under normal conditions of use with adequate ventilation. In case of inadequate ventilation wear respiratory protection. EN 143



#### Environmental exposure controls:

Avoid release to the environment.

#### Other information:

Do not eat, drink or smoke during use. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

.1. Information on basic physical and c	hemical properties	I. Information on basic physical and chemical properties		
Physical state	: Liquid			
Colour	: Blue.			
Odour	: characteristic.			
Odour threshold	: No data available.			
рН	: No data available.			
Relative evaporation rate (butylacetate=1)	: No data available.			
Melting point	: <0°C			
Freezing point	: No data available.			
Boiling point	: > 100 °C			
Flash point	: >65 °C			
Auto-ignition temperature	: No data available.			
Decomposition temperature	: No data available.			
Flammability (solid, gas)	: No data available.			
Vapour pressure	: No data available.			
Relative vapour density at 20 °C	: No data available.			
Relative density	: 1.11 (Water = 1)			
Relative density of saturated gas/air mixture	: > 1 (air =1)			
Solubility	: Moderately soluble in water.			
Log Pow	: No data available.			
Viscosity, kinematic	: No data available.			
Viscosity, dynamic	: No data available.			
Explosive properties	: No data available.			
Oxidising properties	: No data available.			
Explosive limits	: No data available.			

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2016/1179

2. Other information Additional information	: : Contains no or very few volatile organic compounds
ECTION 10: Stability and reac	tivity
0.1. Reactivity	
o additional information available.	
0.2. Chemical stability	
lo additional information available.	
0.3. Possibility of hazardous react	tions
lo additional information available.	
0.4. Conditions to avoid	
void extremely high (> 50 $^{\circ}$ C) or low (<5	5 $^{\circ}$ C) temperatures. Keep away from heat and direct sunlight.
0.5. Incompatible materials	
Dxidizing agents. Strong acid. Alkalines.	
0.6. Hazardous decomposition pro	oducts
No additional information available.	
SECTION 11: Toxicological info	
1.1. Information on toxicological e	
	: Not classified
Acute toxicity (oral)	
Acute toxicity (dermal)	: Not classified
Acute toxicity (dermal) Acute toxicity (inhalation)	: Not classified : Not classified
Acute toxicity (dermal) Acute toxicity (inhalation) reaction product: bisphenol-A-(epic	: Not classified : Not classified hlorhydrin); epoxy resin (number average molecular weight ≤ 700) (25068-38-6)
Acute toxicity (dermal) Acute toxicity (inhalation) reaction product: bisphenol-A-(epic LD50 oral rat	<ul> <li>Not classified</li> <li>Not classified</li> <li>Not classified</li> <li>hlorhydrin); epoxy resin (number average molecular weight ≤ 700) (25068-38-6)</li> <li>15000 mg/kg</li> </ul>
Acute toxicity (dermal) Acute toxicity (inhalation) reaction product: bisphenol-A-(epic LD50 oral rat LD50 dermal rabbit	<ul> <li>Not classified</li> <li>Not classified</li> <li>hlorhydrin); epoxy resin (number average molecular weight ≤ 700) (25068-38-6)</li> <li>15000 mg/kg</li> <li>23000 mg/kg</li> </ul>
Acute toxicity (dermal) Acute toxicity (inhalation) reaction product: bisphenol-A-(epic LD50 oral rat	<ul> <li>Not classified</li> <li>Not classified</li> <li>hlorhydrin); epoxy resin (number average molecular weight ≤ 700) (25068-38-6)</li> <li>15000 mg/kg</li> <li>23000 mg/kg</li> </ul>
Acute toxicity (dermal) Acute toxicity (inhalation) reaction product: bisphenol-A-(epic LD50 oral rat LD50 dermal rabbit oxirane, mono[(C12-14-alkyloxy)met	<ul> <li>Not classified</li> <li>Not classified</li> <li>hlorhydrin); epoxy resin (number average molecular weight ≤ 700) (25068-38-6)</li> <li>15000 mg/kg</li> <li>23000 mg/kg</li> <li>thyl] derivs. (68609-97-2)</li> </ul>
Acute toxicity (dermal) Acute toxicity (inhalation) reaction product: bisphenol-A-(epic LD50 oral rat LD50 dermal rabbit oxirane, mono[(C12-14-alkyloxy)met LD50 oral rat	<ul> <li>Not classified</li> <li>Not classified</li> <li>hlorhydrin); epoxy resin (number average molecular weight ≤ 700) (25068-38-6)</li> <li>15000 mg/kg</li> <li>23000 mg/kg</li> <li>thyl] derivs. (68609-97-2)</li> <li>17100 mg/kg</li> </ul>
Acute toxicity (dermal) Acute toxicity (inhalation) reaction product: bisphenol-A-(epic LD50 oral rat LD50 dermal rabbit oxirane, mono[(C12-14-alkyloxy)met LD50 oral rat Skin corrosion/irritation	<ul> <li>Not classified</li> <li>Not classified</li> <li>hlorhydrin); epoxy resin (number average molecular weight ≤ 700) (25068-38-6)</li> <li>15000 mg/kg</li> <li>23000 mg/kg</li> <li>thyl] derivs. (68609-97-2)</li> <li>17100 mg/kg</li> <li>Causes skin irritation.</li> </ul>
Acute toxicity (dermal) Acute toxicity (inhalation) reaction product: bisphenol-A-(epic LD50 oral rat LD50 dermal rabbit oxirane, mono[(C12-14-alkyloxy)met LD50 oral rat Skin corrosion/irritation Serious eye damage/irritation	<ul> <li>Not classified</li> <li>Not classified</li> <li>hlorhydrin); epoxy resin (number average molecular weight ≤ 700) (25068-38-6)</li> <li>15000 mg/kg</li> <li>23000 mg/kg</li> <li>thyl] derivs. (68609-97-2)</li> <li>17100 mg/kg</li> <li>Causes skin irritation.</li> <li>Causes serious eye irritation.</li> <li>May cause an allergic skin reaction.</li> <li>Not classified</li> </ul>
Acute toxicity (dermal) Acute toxicity (inhalation) reaction product: bisphenol-A-(epic LD50 oral rat LD50 dermal rabbit oxirane, mono[(C12-14-alkyloxy)med LD50 oral rat Skin corrosion/irritation Serious eye damage/irritation Respiratory or skin sensitisation	<ul> <li>Not classified</li> <li>Not classified</li> <li>hlorhydrin); epoxy resin (number average molecular weight ≤ 700) (25068-38-6)</li> <li>15000 mg/kg</li> <li>23000 mg/kg</li> <li>thyl] derivs. (68609-97-2)</li> <li>17100 mg/kg</li> <li>Causes skin irritation.</li> <li>Causes serious eye irritation.</li> <li>May cause an allergic skin reaction.</li> </ul>
Acute toxicity (dermal) Acute toxicity (inhalation) reaction product: bisphenol-A-(epic LD50 oral rat LD50 dermal rabbit oxirane, mono[(C12-14-alkyloxy)met LD50 oral rat Skin corrosion/irritation Serious eye damage/irritation Respiratory or skin sensitisation Germ cell mutagenicity	<ul> <li>Not classified</li> <li>Not classified</li> <li>hlorhydrin); epoxy resin (number average molecular weight ≤ 700) (25068-38-6)</li> <li>15000 mg/kg</li> <li>23000 mg/kg</li> <li>thyl] derivs. (68609-97-2)</li> <li>17100 mg/kg</li> <li>Causes skin irritation.</li> <li>Causes serious eye irritation.</li> <li>May cause an allergic skin reaction.</li> <li>Not classified</li> </ul>
Acute toxicity (dermal) Acute toxicity (inhalation) reaction product: bisphenol-A-(epic LD50 oral rat LD50 dermal rabbit oxirane, mono[(C12-14-alkyloxy)met LD50 oral rat Skin corrosion/irritation Serious eye damage/irritation Respiratory or skin sensitisation Germ cell mutagenicity Carcinogenicity	<ul> <li>Not classified</li> <li>Not classified</li> <li>hlorhydrin); epoxy resin (number average molecular weight ≤ 700) (25068-38-6)</li> <li>15000 mg/kg</li> <li>23000 mg/kg</li> <li>thyl] derivs. (68609-97-2)</li> <li>17100 mg/kg</li> <li>Causes skin irritation.</li> <li>Causes serious eye irritation.</li> <li>Causes serious eye irritation.</li> <li>May cause an allergic skin reaction.</li> <li>Not classified</li> <li>Not classified</li> </ul>
Acute toxicity (dermal) Acute toxicity (inhalation) reaction product: bisphenol-A-(epic LD50 oral rat LD50 dermal rabbit oxirane, mono[(C12-14-alkyloxy)met LD50 oral rat Skin corrosion/irritation Serious eye damage/irritation Respiratory or skin sensitisation Germ cell mutagenicity Carcinogenicity Reproductive toxicity	<ul> <li>Not classified</li> <li>Not classified</li> <li>hlorhydrin); epoxy resin (number average molecular weight ≤ 700) (25068-38-6)</li> <li>15000 mg/kg</li> <li>23000 mg/kg</li> <li>thyl] derivs. (68609-97-2)</li> <li>17100 mg/kg</li> <li>Causes skin irritation.</li> <li>Causes serious eye irritation.</li> <li>Causes serious eye irritation.</li> <li>May cause an allergic skin reaction.</li> <li>Not classified</li> <li>Not classified</li> <li>Not classified</li> <li>Not classified</li> <li>Not classified</li> <li>Not classified</li> </ul>

2.1. Toxicity	
Ecology - general	: Toxic to aquatic life with long lasting effects.
Acute aquatic toxicity	: Not classified
Chronic aquatic toxicity	: Toxic to aquatic life with long lasting effects.
	: Toxic to aquatic life with long lasting effects. orhydrin); epoxy resin (number average molecular weight ≤ 700) (25068-38-6) 96hr 2 mg/l leuciscus idus
reaction product: bisphenol-A-(epichle	orhydrin); epoxy resin (number average molecular weight ≤ 700) (25068-38-6)

No additional information available.

Bioaccumulative potential

2-(chloromethyl)oxirane; Formaldehyde; Pher	nol (28064-14-4)
Log Pow	3

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2016/1179

2-(chloromethyl)oxirane; Formaldehyde; Phenol (28064-14-4)			
Bioaccumulative potential	Potentially bioaccumulable.		
oxirane, mono[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)			
Bioconcentration factor (BCF REACH)	934.9		
Log Kow	7.25		
oxirane, mono[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)			
oxirane, mono[(C12-14-alkyloxy)methyl] o Log Koc	derivs. (68609-97-2) 12830		
	12830		
Log Koc	12830		
Log Koc 2.5. Results of PBT and vPvB assessm	12830		

Additional information

: Avoid release to the environment.

SECTION 13: Disposal considerations			
13.1. Waste treatment methods			
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.		
Additional information	: Empty containers should be taken for recycle, recovery or waste in accordance with local regulation.		
Ecology - waste materials	: Avoid release to the environment.		

### **SECTION 14: Transport information**

In accordance with ADR / RID / IMDG / IATA / ADN

n accordance with ADR / RIE	) / IMDG / IATA / ADN			
ADR	IMDG	IATA	ADN	RID
14.1. UN number	·			
3082	3082	3082	3082	3082
14.2. UN proper shipp		·	·	
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS : reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700))	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS : reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700))	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS : reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700))	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS : reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700))	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS : reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700))
UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS : reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)), 9, III, (-)	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS : reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)), 9, III, MARINE POLLUTANT	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS : reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS : reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS : reaction product: bisphenoI-A- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)), 9, III
14.3. Transport hazard	d class(es)		<u> </u>	
9	9	9	9	9
14.4. Packing group		· • • •	· • •	· · ·
III	III	III	III	III
14.5. Environmental h		1	1	1
Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes
		nalish)	•	•

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2016/1179

ADR IMDG	ΙΑΤΑ	ADN	RID	
	No supplementary information			
4.6. Special precautions for user				
- Overland transport Classification code (ADR)	: M6			
Special provisions (ADR)				
Limited quantities (ADR)	: 274, 335, 375, 601 : 5l			
Excepted quantities (ADR)	: E1			
Packing instructions (ADR)	: P001, IBC03, LP01, R001			
Special packing provisions (ADR)	: PP1			
Mixed packing provisions (ADR)	: MP19			
Portable tank and bulk container instructions	: T4			
(ADR)				
Portable tank and bulk container special provisions (ADR)	: TP1, TP29			
Tank code (ADR)	: LGBV			
Vehicle for tank carriage	: AT			
Transport category (ADR)	: 3			
Special provisions for carriage - Packages (ADR)	: V12			
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV13			
Hazard identification number (Kemler No.)	: 90			
Orange plates	90 3082			
Tunnel restriction code (ADR)	: -			
EAC code	: •3Z			
- Transport by sea				
Special provisions (IMDG)	: 274, 335, 969			
Limited quantities (IMDG)	: 5 L			
Excepted quantities (IMDG)	: E1			
Packing instructions (IMDG)	: LP01, P001			
Special packing provisions (IMDG)	: PP1			
IBC packing instructions (IMDG)	: IBC03			
Tank instructions (IMDG)	: T4			
Tank special provisions (IMDG)	: TP2, TP29			
EmS-No. (Fire)	: F-A			
EmS-No. (Spillage)	: S-F			
Stowage category (IMDG)	: A			
- Air transport				
PCA Excepted quantities (IATA)	: E1			
PCA Limited quantities (IATA)	: Y964			
PCA limited quantity max net quantity (IATA)	: 30kgG			
PCA packing instructions (IATA)	: 964			
PCA max net quantity (IATA)	: 450L			
CAO packing instructions (IATA)	: 964			
CAO max net quantity (IATA)	: 450L			
Special provisions (IATA)	: A97, A158, A197			
ERG code (IATA)	: 9L			
- Inland waterway transport				
Classification code (ADN)	: M6			
Special provisions (ADN)	: 274, 335, 375, 601			
Limited quantities (ADN)	: 5 L			

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2016/1179

~ `			amonanion (20) 2010, 111
	Excepted quantities (ADN)	:	E1
	Carriage permitted (ADN)	:	Т
	Equipment required (ADN)	:	PP
	Number of blue cones/lights (ADN)	:	0
	- Rail transport		
	Classification code (RID)	:	M6
	Special provisions (RID)	:	274, 335, 375, 601
	Limited quantities (RID)	:	5L
	Excepted quantities (RID)	:	E1
	Packing instructions (RID)	:	P001, IBC03, LP01, R001
	Special packing provisions (RID)	:	PP1
	Mixed packing provisions (RID)	:	MP19
	Portable tank and bulk container instructions (RID)	:	Τ4
	Portable tank and bulk container special provisions (RID)	:	TP1, TP29
	Tank codes for RID tanks (RID)	:	LGBV
	Transport category (RID)	:	3
	Special provisions for carriage – Packages (RID)	:	W12
	Special provisions for carriage - Loading, unloading and handling (RID)	:	CW13, CW31
	Colis express (express parcels) (RID)	:	CE8
	Hazard identification number (RID)	:	90

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

### SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Seveso Information

: E2 Hazardous to the Aquatic Environment in Category Chronic 2

#### 15.1.2. National regulations

No additional information available.

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

### **SECTION 16: Other information**

Abbreviations and acronyms:			
SDS	Safety Data Sheet		
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008		
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006		
PBT	Persistent Bioaccumulative Toxic		
vPvB	Very Persistent and Very Bioaccumulative		
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways		
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road		
IATA	International Air Transport Association		
IMDG	International Maritime Dangerous Goods		
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail		
LC50	Median lethal concentration		
LD50	Median lethal dose		
CAS	CAS (Chemical Abstracts Service) number		
EG-nr	EINECS- en ELINCS-number		

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2016/1179

EINECS	European Inventory of Existing Commercial Substances	
OEL	Occupational Exposure Limit	
Data sources	: according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2016/1179.	
Other informatio	n : REACH Disclaimer: This information is based on current knowledge. Consistency of data in the SDS with CSR is considered, as far as the information is available at the time of compilation (cfr Revision date and Version number). DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.	

#### Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4		
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2		
Aquatic Chronic 3	Hazardous to th	ne aquatic environment — Chronic Hazard, Category 3	
Eye Dam. 1	Serious eye dar	mage/eye irritation, Category 1	
Eye Irrit. 2	Serious eye dar	mage/eye irritation, Category 2	
Skin Irrit. 2	Skin corrosion/i	rritation, Category 2	
Skin Sens. 1	Skin sensitisation, Category 1		
H312	Harmful in contact with skin.		
H315	Causes skin irritation.		
H317	May cause an allergic skin reaction.		
H318	Causes serious eye damage.		
H319	Causes serious eye irritation.		
H411	Toxic to aquatic life with long lasting effects.		
H412	Harmful to aquatic life with long lasting effects.		
Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:			
Skin Irrit. 2	H315 Calculation method		
Eye Irrit. 2	H319 Calculation method		
Skin Sens. 1	H317 Calculation method		
Aquatic Chronic 2	H411 Calculation method		

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.