



WOOD FINISHES DIRECT

The following Product Datasheet is provided by **Ronseal**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:
[Ronseal Garden Paint](#)

PRODUCT DATA SHEET

RONSEAL GARDEN PAINT

Ronseal Garden Paint is a product designed to add colour and protection to a wide range of garden surfaces. Ronseal Garden Paint is rainproof in 1 hour and can be used to colour and protect wood, brick, terracotta, metal and stone.

INTRODUCTION

Ronseal Garden Paint is formulated to provide a wide range of garden surfaces with a highly waterproof and durable coating, which will resist the elements and prevent damage. The blend of inorganic and organic UV resistant pigments provide a high quality, long lasting and attractive colour. When applied to wood the colour is guaranteed for 5 years.

Ronseal Garden Paint is safe to use around plants and animals. Its low odour, quick drying formulation makes it convenient and pleasant to use and ensures surfaces will be rainproof one hour after the application of the recommended three coats.

Ronseal Garden Paint is available in a range of classic and contemporary colours, which result in a high opacity matt finish. It can be applied to bare or previously painted surfaces although bare metal will require the use of a suitable primer.

COMPOSITION

Ronseal Garden Paint is a water based vinyl acetate co-polymer emulsion incorporating inorganic and organic pigments.

PROPERTIES

Appearance	Viscous liquid.
Odour	Low, typical acrylic.
VOC content	Low (0.30% to 7.99% w/v)
Miscible with water.	

FIELDS OF APPLICATION

Ronseal Garden Paint is ideal for use on most garden surfaces. It can be used on both rough sawn and smooth planed wood, brick, terracotta, metal and stone.

It can be applied to bare or previously painted surfaces.

Ronseal Woodland Trust Colours is not suitable for use on plastic, cast iron, decking or any areas that will be subject to foot traffic.

PREPARATION

Ensure surfaces are clean and dry prior to application. Ronseal Garden Paint should be applied in dry conditions and at temperatures above 10°C.

Wood:

On smooth planed, weathered and previously painted wood, sand to remove any loose wood fibres or paint and wipe off any dirt, dust and grease with white spirit. Other finishes such as varnish or stain must be completely removed before application. To avoid resin bleed through resinous knots should be treated with Ronseal Exterior Knot Block Primer prior to painting.

New wood should be lightly sanded then washed with white spirit and allowed to dry.

For rough sawn timber, remove any dirt, moss, fungal growth and lichens with a stiff brush.

Metal:

Remove any rust or loose paint by thoroughly wire brushing the surface. Remove any sanding dust or dirt by wiping with white spirit.

Any bare metal must be primed with a suitable metal primer prior to application of Ronseal Garden Paint.

Brick, Terracotta & Stone:

Remove any dirt or loose material with a wire brush. Wipe or brush to remove any dust. Terracotta pots make need thorough sanding/wire brushing to improve adhesion. Splash the pot with some water, if beading of the water is evident further sanding is required.

In all cases the treatment of a test area to confirm colour suitability is recommended.

APPLICATION

Stir thoroughly prior to and during use.

Do not apply in wet conditions or if rain is likely before the product dries. Do not apply at temperatures below 10°C or in high humidity. Do not apply in direct sunlight.

For best possible results use a good quality brush designed for the application of water based finishes.

Apply even coats brushing in the direction of the grain when applying to wood.

Apply three coats allowing four hours between coats. On smooth surfaces lightly sand between the second and third coats.

Allow 24-48 hours after the application of the final coat before using garden furniture.

Ronseal Garden Paint is safe for use with plants and pets. If plants are splashed during application wipe off with a damp cloth before it dries. Keep animals away from treated areas until dry.

COVERAGE

Up to 12 square metres per litre per coat. Coverage will be significantly reduced on rough sawn timber and other textured surfaces.

DRYING TIME

All 4 hours between coats and the product will be rainproof 1 hour after application of the final coat.

Low temperatures and high humidity will lengthen the drying time.

Allow coating to dry thoroughly before placing soft furnishings.

CLEANING OF TOOLS

All tools and equipment should be cleaned immediately after use by washing in water and detergent.

Remove as much product as possible from tools and equipment before washing.

Wipe the container and lid rim with a clean cloth prior to resealing the pack.

IMPORTANT NOTES

Apply in accordance with the coverage guidelines otherwise product performance will be reduced.

Always test a small area prior to full application to confirm colour suitability and level of adhesion. The final colour will be influenced by the texture, grain, colour, porosity and type of wood as well as the number of coats applied.

Do not apply in temperatures below 10°C or in conditions of high humidity or if rain is likely before the product has fully dried.

Avoid the inhalation of dust when sanding, wear a suitable face mask or employ wet sanding techniques.

Allow coating to dry thoroughly before placing soft furnishings in contact with the wood (48 hours).

STORAGE

Store in a cool, dry, well ventilated place away from heat and sources of ignition. Carefully reseal partly used containers. Do not store near foodstuffs. Protect from frost.

To avoid risk of spillage, always store and transport in a secure and upright position.

The shelf life of the product in airtight containers is at least three years.

HEALTH AND SAFETY

Observe and follow all warnings and instructions for use shown on the pack.

Specific safety data sheets are available on request.

FLAMMABILITY

Non-flammable.

SUPPLY

Obtainable from selected DIY retailers.

SIZES

Available in sizes ranging from 250 ml to 5 litre in re-sealable containers. Some colours may not be available in all sizes.

DISPOSAL

Some local authorities have special facilities for disposal of waste paints.

Do not empty product into drains or watercourses.

LIABILITY

Whilst these specifications are based on expert technical knowledge and practical experience, we cannot assume responsibility for any work as the ultimate result depends on factors beyond our direct control. Standard codes of painting practice should be followed.

INFORMATION AND SERVICE

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require.

DATA SHEETS

Data sheets on other Ronseal Products are available on request from our Technical Services Department.

Sherwin-Williams Diversified Brands Ltd operates a quality management system that complies with the requirements of ISO 9000:2008 (Certificate No. FM 01669).

Sherwin-Williams Diversified Brands Ltd operates an Environmental Management System that complies with the requirements of ISO 14001:2004 (Certificate No. EMS 35924).

Sherwin-Williams Diversified Brands Ltd
Thornccliffe Park
Chapelton
Sheffield
S35 2YP

Tel: +44(0)114 246 7171

Fax: +44(0)114 245 5629

Registered in England 2968830

E. Mail: enquiry@ronseal.co.uk

Website: www.ronseal.co.uk

Ronseal is a Registered Trademark of the Sherwin-Williams Company.

Issue 1 November 2016