



**WOOD  
FINISHES  
DIRECT**



Finish. Finished.

The following Product Datasheet is provided by **Ronseal**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:

[Ronseal Super Flexible Primer and Undercoat](#)

# PRODUCT DATA SHEET

No. 11192

JANUARY 2011

## RONSEAL SUPER FLEXIBLE WOOD PRIMER & UNDERCOAT

Ronseal Super Flexible Wood Primer & Undercoat adheres superbly to wood and both primes and undercoats in one, providing the ultimate basecoat for any topcoat finish.

### INTRODUCTION

Ronseal Super Flexible Wood Primer & Undercoat improves the performance of exterior topcoat gloss paint. When used with Ronseal 7 Year Wood Paint it is guaranteed to last 7 years.

The highly pigmented formula of Ronseal Super Flexible Wood Primer & Undercoat provides excellent hiding power and is so flexible that it moves with the wood to maintain adhesion to help prevent cracking and peeling of the topcoat.

Ronseal Super Flexible Wood Primer & Undercoat has an advanced stain locking composition that stops extractives and tannins found in resinous woods from staining through to the topcoat.

### COMPOSITION

Ronseal Super Flexible Wood Primer & Undercoat is a water based polyurethane-acrylic formula.

### PROPERTIES

Appearance – Structured Liquid.  
VOC Content – Low (0.3-7.99% w/v)  
Odour – Low, inoffensive.  
Non Flammable.  
Miscible with water.

### FIELDS OF APPLICATION

Ronseal Super Flexible Wood Primer & Undercoat can be used on wooden doors, window frames, cladding and fascias.

Ronseal Super Flexible Wood Primer & Undercoat is ideal for use with resinous hardwoods such as Mahogany, Oak and teak.

### PREPARATION

Do not apply this product in damp conditions or if temperature is below 10°C.

Make sure the wood surface to be treated is clean, dry and free from dirt, dust and grease.

#### ***Bare Wood***

Lightly sand to remove any loose fibres and wipe clean. Fill in any small holes or surface defects with Ronseal Multi Purpose Wood Filler.

#### ***Previously Painted Wood***

Sand down to remove any flaking or blistered paint. Paintwork that is in sound condition should be sanded first to provide a key. Ensure the wood is clean by wiping with white spirit to remove any dust. Avoid inhalation of dust, wear a suitable face mask when sanding.

#### ***Unsound Wood***

Use Ronseal High Performance Wood Filler to repair any damaged areas and replace any rotten wood with sound timber, then treat as bare wood.

### APPLICATION

Stir the paint thoroughly before use. Apply two coats evenly using a good quality synthetic brush, finishing in the direction of the grain. When using more than one tin, intermix before use to ensure an even colour.

Apply a second coat after four hours.

### COVERAGE

Approximately 25 square metres per litre.

Coverage will vary dependent upon the absorbency and texture of the substrate. Apply in accordance with the coverage guidelines or performance will be impaired.

### DRYING TIME

Touch dry in 1hour. Overcoatable after 6 hours.

Poor ventilation, low temperatures and high humidity will lengthen drying times.

### CLEANING OF TOOLS

Remove as much paint as possible from tools and equipment before cleaning.

Clean brushes with water and detergent.

Some local authorities have special facilities for disposing of waste coatings. Do not empty into drains or watercourses.

### IMPORTANT NOTES

Always pre-test on a small area first to confirm colour acceptability.

Use product only as directed.

Apply in accordance with the coverage guidelines otherwise product performance will be reduced.

Do not apply if the room temperature is below 10°C during application and drying or in conditions of high humidity.

## STORAGE

Store in a cool, dry, well ventilated place away from heat and sources of ignition. Carefully reseal partly used containers. Do not store near foodstuffs. Protect from frost.

To avoid risk of spillage, always store and transport in a secure and upright position.

## HEALTH AND SAFETY

Keep out of reach of children.

Observe and follow all warnings and instructions for use shown on the pack.

Avoid contact with skin and eyes.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After contact with skin, wash immediately with plenty of soap and water.

Use only in well ventilated areas.

Specific health and safety data sheets are available on request.

## SUPPLY

Obtainable from DIY retailers.

## SIZES

Available in 750ml resealable containers.

## DISPOSAL

Some local authorities have special facilities for disposal of waste coatings.

Do not empty product into drains or watercourses.

## LIABILITY

Whilst these specifications are based on expert technical knowledge and practical experience, we cannot assume responsibility for any work as the ultimate result depends on factors beyond our direct control. Standard codes of painting practice should followed.

## INFORMATION AND SERVICE

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require.

## DATA SHEETS

Data sheets on other Ronseal Products are available on request from our Technical Services Department.

Ronseal Ltd. has been registered to BS EN ISO 9000 1994 (Registered Firm No. FM 1669/1).

Ronseal Ltd. operate an Environmental Management System that complies with the requirements of BS 7750:1994, Certificate No. EMS 35924

Ronseal Ltd. has achieved Investors in People certification, (certificate number 59586).

**©RONSEAL LTD.,**  
**Thornccliffe Park,**  
**Chapelton,**  
**Sheffield.**  
**S35 2YP**

**Tel:**  
**+44 (0114) 240 9469 (Technical Services)**  
**+44 (0114) 246 7171 (Main Switchboard)**  
**Fax:**  
**+44 (0114) 245 5629**

**E. Mail:** [enquiry@ronseal.co.uk](mailto:enquiry@ronseal.co.uk)

**Website:** [www.ronseal.co.uk](http://www.ronseal.co.uk)

Ronseal is a registered trademark of the Sherwin Williams Company.

JANUARY, 2011. ISSUE 1

