



**WOOD
FINISHES
DIRECT**



Finish. Finished.

The following Product Datasheet is provided by **Ronseal**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:

[Ronseal Ultimate Protection Decking Oil](#)

PRODUCT DATA SHEET

No. 11430

JANUARY 2013

RONSEAL ULTIMATE PROTECTION DECKING OIL

Ronseal Ultimate Protection Decking Oil lasts twice as long as standard decking oils to provide ultimate nourishment and protection while enhancing the natural colour of decking.

INTRODUCTION

Ronseal Ultimate Protection Decking Oil provides superior, natural looking protection for a longer lasting finish.

Ronseal Ultimate Protection Decking Oil provides optimum weather protection, increased foot traffic resistance and superior nourishment.

Ronseal Ultimate Protection Perfect Finish Oil's unique formula penetrates deeper into the wood to provide increased durability. Providing a lightly tinted finish it will give double the weather resistance and foot traffic protection versus standard decking oils (based on weathering data).

PROPERTIES

Viscosity - Low.

Odour - Low.

VOC Content – Low (0.3% to 7.99%)

Solubility - miscible with water.

Flash Point - >60CC (Closed cup).

COMPOSITION

Alkyd acrylic technology in a water thinnable linseed oil.

FIELDS OF APPLICATION

Ronseal Ultimate Protection Decking Oil is recommended for use on smooth planed hard and softwood decking constructed using good quality specially pre-treated, pressure treated or preservative impregnated timber.

PREPARATION

For untreated grey and weathered wood use Ronseal Decking Restorer to restore the deck's natural colour and provide a sound base for application which ensures the stain penetrates effectively.

Previously finished decking: Use Ronseal Decking Cleaner & Reviver to remove any dust, grease, oil, mildew, algae and other contaminants. Remove any loose, flaking, or peeling coatings. To avoid patchiness remove all previous coatings using Ronseal Decking Stripper. Ensure cut ends are adequately protected using Ronseal Decking End Grain Preserver.

New decking should be allowed to weather naturally for at least six months.

Clean the deck with Ronseal Decking Cleaner & Reviver using a scrubbing brush to open the pores of the wood and remove any contamination. Rinse thoroughly with clean water ideally using a pressure washer. Allow to dry fully before overcoating. Test effectiveness of the cleaning by splashing the deck with water. If beading occurs, re-clean. Retest before applying any oil.

The shade label indicates approximate colour only. We recommend you test a small area to determine the final colour which may be influenced by the texture, grain, colour, porosity, type of wood and previous treatment.

APPLICATION

Ensure decking is thoroughly dry. Do not apply in damp conditions or when rain is likely before product has dried. Do not apply below 10°C.

Remove the overcap and assemble the pad. Remove the lid which can be used as a tray if required. Stir thoroughly then pour approximately 1 to 1.5cm into the tray. Do not dilute.

Dip the pad into the stain, ensuring the underside of the pad is immersed. Do not overload it.

Apply liberally to ensure even penetration and complete coverage of the decking is achieved.

Starting in the furthest corner push or pull the pad in the direction of the grain. The pad will hold more stain than a brush allowing you to apply the stain in long, effortless strokes. Work away excess stain and redistribute it evenly along the decking board to ensure it doesn't puddle in the grooves.

When applying to deck boards treat 3-4 boards at a time to avoid lap marks.

Apply two coats, allowing four hours between coats.

COVERAGE

One 2.5L container will cover approximately 10-12 with two coats. Coverage will vary with absorbency and profile of the deck.

DRYING TIME

Ronseal Ultimate Protection Decking Oil will be rainproof in 90 minutes. Allow 4 hours before light foot traffic and 24 hours or overnight before heavy traffic.

CLEANING OF TOOLS

Clean equipment with warm, soapy water.

MAINTENANCE

Decking treated with Ronseal Ultimate Protection Decking Oil may be cleaned using Ronseal Decking Cleaner & Reviver. The coating should be inspected on an annual basis and be re-coated as appropriate.

IMPORTANT NOTES

Ronseal Ultimate Protection Decking Oil is intended for use on decking constructed from good quality, specially pre-treated, pressure treated or preservative impregnated hard or softwood.

Do not use Ronseal Ultimate Protection Decking Oil if rain is imminent.

Decking boards should be completely dry before application.

Do not use Ronseal Ultimate Protection Decking Oil in temperatures below 10°C.

Thoroughly remove all previous coating prior to application or Ronseal Ultimate Protection Decking Oil.

Some pre-treatments may effect adhesion of decking products. Test by splashing water on timber, if beading occurs, allow a period of weathering and re-test prior to application. Always test on a small area prior to proceeding to confirm colour suitability and adhesion.

STORAGE

Store upright and carefully re-seal partly used containers.

Protect from frost.

HEALTH AND SAFETY

Observe and follow all warnings and instructions for use shown on the pack.

Non-Flammable.

Harmful to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

Keep out of reach of children.

Avoid contact with the skin and eyes. Wear suitable gloves.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After contact with skin, wash immediately with plenty of soap and water or a proprietary skin cleanser. Do not use solvents or thinners/white spirit.

Use only in well ventilated areas.

Contains alpha-3-(3-(2H-BENZOTRIAZOL...MIXTURE E C INDEX 607-176-00-3,bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate.

May produce an allergic reaction.

Specific health and safety data sheets are available on request.

FLAMMABILITY

Non-Flammable.

SUPPLY

Obtainable from DIY retailers, paint suppliers and builders merchants.

SIZES

Obtainable in 2.5 litre resealable containers.

DISPOSAL

Some local authorities have special facilities for the disposal of waste products.

Do not empty into drains or watercourses.

LIABILITY

Whilst these specifications are based on expert technical knowledge and practical experience, we cannot assume responsibility for any work as the ultimate results depend on factors beyond our direct control. Standard codes of painting practice should be followed.

INFORMATION AND SERVICE

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require.

DATA SHEETS

Data sheets on other Ronseal products are available on request from our Technical Services Department.

Ronseal Ltd. has been registered to BS EN ISO 9000 1994 (Registered Firm No. FM 1669/1).

Ronseal Ltd. operates an Environmental Management System that complies with the requirements of BS 7750:1994, certificate No. EMS 35924.

Ronseal Ltd. has achieved Investors in People certification, (certificate number 59586).

©RONSEAL LTD.,

**Thorncliffe Park,
Chapelton,
Sheffield.
S35 2YP**

Tel:

+44 (0114) 240 9469 (Technical Services)

+44 (0114) 246 7171 (Main Switchboard)

Fax:

+44 (0114) 245 5629

E. Mail: enquiry@ronseal.co.uk

Website: www.ronseal.co.uk

Ronseal is a registered trademark of the Sherwin Williams Company.

JANUARY 2013. ISSUE 1