



**WOOD  
FINISHES  
DIRECT**



Finish. Finished.

The following Product Datasheet is provided by **Ronseal**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:  
[Ronseal Hardwood Furniture Oil Spray](#)

# PRODUCT DATA SHEET

## RONSEAL HARDWOOD GARDEN FURNITURE OIL AEROSOL

Ronseal Hardwood Garden Furniture Oil is formulated to protect nourish and waterproof exterior hardwood furniture. Ronseal Hardwood Garden Furniture Oil comes in a convenient aerosol and dries to a non-glossy finish which enriches the natural colour of the hardwood.

### INTRODUCTION

Ronseal Hardwood Garden Furniture Oil is formulated to replace essential oils necessary to prevent wood from drying, warping and splitting. Ronseal Hardwood Garden Furniture Oil also contains additives to prevent the wood from greying.

Ronseal Hardwood Garden Furniture Oil dries to a non-glossy finish that enriches the natural colour of the hardwood. It is suitable for use on all exterior bare hardwoods including teak, oak and mahogany.

### COMPOSITION

A blend of linseed and tung oil and resins in hydrocarbon solvent.

### PROPERTIES

Appearance-Low viscosity liquid.  
Colour -Light to medium brown.  
Odour-Characteristic solvent type.  
Solubility-Immiscible with water.  
VOC Content- Very High (>50%w/v).  
Extremely Flammable Aerosol.

### FIELDS OF APPLICATION

Ronseal Hardwood Garden Furniture Oil can be applied to all types of bare hardwood garden furniture.

### PREPARATION

Previous coatings such as wax, polish or lacquer should be removed using Colron Wax Remover. Paint or varnish must be removed using Colron Furniture Stripper prior to application.

Ensure all surfaces are clean and dry and ensure it's a warm, still and dry day. Wearing an appropriate face mask to prevent the inhalation of dust lightly sand and wipe with white spirit. Ensure adjacent areas are adequately protected from overspray.

### APPLICATION

Shake well prior to use. Ensure the area is well ventilated during application and drying. Test the colour and practise on a small, preferably hidden, area first. Spray 20-30cm from the surface in a sweeping motion. After 15 minutes wipe off any excess oil with a lint free cloth\*.

For best result apply three coats allowing 6 hours between coats.

### DRYING TIME

6 hours between coats but allow 24 hours after the final coat before replacing any soft furnishings and use.

### CLEAN-UP

\*Cloths and soiled rags may self-ignite without warning. Wash out well in warm soapy water before disposal.

Remove as much product as possible from cloths prior to cleaning.

### MAINTENANCE

Apply further coats as required as directed above, retreatment on an annual basis is recommended.

### IMPORTANT NOTES

Refer to instructions on the pack prior to use.

For best results apply to bare wood.

Cloths and soiled rags may self-ignite without warning. Wash out well in warm soapy water before disposal.

Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood as they may contain harmful lead. For further advice contact Ronseal Technical Services.

Ronseal Hardwood Garden Furniture Oil may darken lighter woods also test on a small inconspicuous areas to confirm colour suitability.

Solvent abuse can kill instantly. For use only as directed.

### STORAGE

Store upright in a cool, dry, well ventilated area away from heat and sources of ignition.

Always store in ambient conditions away from temperature extremes. Protect from frost. Store above 5°C.

### HEALTH AND SAFETY

Observe and follow all warnings and instructions for use shown on the pack.

Specific health and safety data sheets are available on request.

### FLAMMABILITY

Extremely Flammable Aerosol.  
Flashpoint ~-18°C

### SUPPLY

Obtainable from DIY retailers, paint suppliers and builders merchants.

### SIZES

Available in a 500ml aerosol.

#### **DISPOSAL**

Some local authorities have special facilities for disposal of waste products.

#### **LIABILITY**

Whilst these specifications are based on expert technical knowledge and practical experience, we cannot assume responsibility for any work as the ultimate results depend on factors beyond our direct control. Standard codes of painting practice should be followed.

#### **INFORMATION AND SERVICE**

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require.

#### **DATA SHEETS**

Data sheets on other Ronseal products are available on request from our Technical Services Department.

Sherwin-Williams Diversified Brands Ltd operates a quality management system that complies with the requirements of ISO 9000:2008 (Certificate No. FM 01669).

Sherwin-Williams Diversified Brands Ltd operates an Environmental Management System that complies with the requirements of ISO 14001:2004 (Certificate No. EMS 35924).

**Sherwin-Williams Diversified Brands Ltd**  
**Thornccliffe Park**  
**Chapelton**  
**Sheffield**  
**S35 2YP**

Tel: +44(0)114 246 7171

Fax: +44(0)114 245 5629

*Registered in England 2968830*

E. Mail: [enquiry@ronseal.co.uk](mailto:enquiry@ronseal.co.uk)

Website: [www.ronseal.co.uk](http://www.ronseal.co.uk)

Ronseal is a Registered Trademark of the Sherwin-Williams Company.

JANUARY 2017. ISSUE 1