



# WOOD FINISHES DIRECT

The following Product Datasheet is provided by **Ronseal**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:

[Ronseal 10 Year Exterior Wood Paint - Gloss](#)

# PRODUCT DATA SHEET

No. 11189

AUGUST 2012

## RONSEAL 10 YEAR WEATHERPROOF WOOD PAINT

Ronseal 10 Year Weatherproof Wood Paint is guaranteed to last for 10 years and will adhere to all bare or previously painted wood.

### INTRODUCTION

Ronseal 10 Year Weatherproof Wood Paint ensures a longer lasting, wood paint finish.

Ronseal 10 Year Weatherproof Wood Paint flexes with the movement of the wood to resist cracking, peeling and blistering. The 10 year formula also resists the damaging effects of the weather to maintain gloss levels longer.

Ronseal 10 Year Weatherproof Wood Paint is drip resistant and brushes out smoothly and evenly to provide excellent protection.

### COMPOSITION

Ronseal 10 Year Weatherproof Wood Paint is a water based polyurethane-acrylic formula.

### PROPERTIES

Appearance – Structured Liquid.  
VOC Content – Low (0.3-7.99% w/v)  
Odour – Low, inoffensive.  
Non Flammable.  
Miscible with water.

### FIELDS OF APPLICATION

Ronseal 10 Year Weatherproof Wood Paint is developed for use on all exterior wood surfaces including wooden doors, window frames, cladding, soffits and fascias.

### PREPARATION

Do not apply this product in damp conditions or if temperature is below 10°C. Make sure the wood surface to be treated is clean, dry and free from dirt, dust and grease.

#### **Bare Wood**

Lightly sand to remove any loose fibres and wipe clean. Fill in any small holes or surface defects with Ronseal Multi Purpose Wood Filler. Treat any knots with Colron Knotting Solution then apply Ronseal Super Flexible Wood Primer & Undercoat.

#### **Previously Painted Wood**

Sand down to remove any flaking or blistered paint. Paintwork that is in sound condition should be sanded first to provide a key. Ensure the wood is clean by wiping with white spirit to remove any dust. Avoid inhalation of dust, wear a suitable face mask when sanding.

#### **Unsound Wood**

Use Ronseal High Performance Wood Filler to repair any damaged areas and replace any rotten wood with sound timber, then treat as bare wood.

### APPLICATION

Stir the paint thoroughly before use. Apply using a good quality synthetic brush, finishing in the direction of the grain. When using more than one tin, intermix before use to ensure an even colour.

Apply a second coat after four hours.

### COVERAGE

2.5l will cover approximately 33m<sup>2</sup> of wood when applying two coats.

Coverage will vary dependent upon the absorbency and texture of the substrate. Apply in accordance with the coverage guidelines or performance will be impaired.

### DRYING TIME

Touch dry in 1-2 hours. Overcoatable after 4 hours.

Poor ventilation, low temperatures and high humidity will lengthen drying times.

### CLEANING OF TOOLS

Remove as much paint as possible from tools and equipment before cleaning.

Clean brushes with water and detergent.

Some local authorities have special facilities for disposing of waste coatings. Do not empty into drains or watercourses.

### IMPORTANT NOTES

Always pre-test on a small area first to confirm colour acceptability.

Use product only as directed.

Apply in accordance with the coverage guidelines otherwise product performance will be reduced.

Do not apply if the room temperature is below 10°C during application and drying or in conditions of high humidity.

### STORAGE

Store in a cool, dry, well ventilated place away from heat and sources of ignition. Carefully reseal partly used containers. Do not store near foodstuffs. Protect from frost.

To avoid risk of spillage, always store and transport in a secure and upright position.

## HEALTH AND SAFETY

Not flammable.

Keep out of reach of children.

Observe and follow all warnings and instructions for use shown on the pack.

Avoid contact with skin and eyes.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After contact with skin, wash immediately with plenty of soap and water.

Use only in well ventilated areas.

Protect from frost – do not apply below 10°C or in high humidity.

Specific health and safety data sheets are available on request.

## SUPPLY

Obtainable from DIY retailers.

## SIZES

Available in 2.5 Litre resealable containers.

## DISPOSAL

Some local authorities have special facilities for disposal of waste coatings.

Do not empty product into drains or watercourses.

## LIABILITY

Whilst these specifications are based on expert technical knowledge and practical experience, we cannot assume responsibility for any work as the ultimate result depends on factors beyond our direct control. Standard codes of painting practice should followed.

## INFORMATION AND SERVICE

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require.

## DATA SHEETS

Data sheets on other Ronseal Products are available on request from our Technical Services Department.

Ronseal Ltd. has been registered to BS EN ISO 9000 1994 (Registered Firm No. FM 1669/1).

Ronseal Ltd. operate an Environmental Management System that complies with the requirements of BS 7750:1994, Certificate No. EMS 35924

Ronseal Ltd. has achieved Investors in People certification, (certificate number 59586).

**©RONSEAL LTD.,**  
**Thornccliffe Park,**  
**Chapelton,**  
**Sheffield.**  
**S35 2YP**

**Tel:**  
**+44 (0114) 240 9469 (Technical Services)**  
**+44 (0114) 246 7171 (Main Switchboard)**  
**Fax:**  
**+44 (0114) 245 5629**

**E. Mail:** [enquiry@ronseal.co.uk](mailto:enquiry@ronseal.co.uk)  
**Website:** [www.ronseal.co.uk](http://www.ronseal.co.uk)

Ronseal is a registered trademark of the Sherwin Williams Company.

AUGUST, 2012. ISSUE 1

