



WOOD FINISHES DIRECT

The following Safety Datasheet is provided by **Rustins**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:
[Rustins Textured Decking Oil](#)



SAFETY DATA SHEET

TEXTURED DECKING OIL

Page: 1

Compilation date: 12/12/2014

Revision date: 03/12/13

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: TEXTURED DECKING OIL

Synonyms: TEXTURED DECKING OIL

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: Rustins Ltd

Waterloo Road

Cricklewood

London

NW2 7TX

United Kingdom

Tel: +44 (0)208 450 4666

Fax: +44 (0)208 452 2008

Email: rustins@rustins.co.uk

1.4. Emergency telephone number

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: -: R10; Sens.: R43; -: R52/53; -: R66

Classification under CLP: Flam. Liq. 3: H226; Skin Sens. 1: H317; Aquatic Chronic 3: H412; -: EUH208

Most important adverse effects: Flammable. May cause sensitisation by skin contact. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Repeated exposure may cause skin dryness or cracking.

2.2. Label elements

Label elements under CLP:

Hazard statements: EUH208: Contains zirconium drier 18%, cobalt 6 (clp format), byk 204, methyl ethyl ketoxime. May produce an allergic reaction.

H226: Flammable liquid and vapour.

H317: May cause an allergic skin reaction.

H412: Harmful to aquatic life with long lasting effects.

Signal words: Warning

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark

[cont...]

SAFETY DATA SHEET

TEXTURED DECKING OIL

Page: 2



Precautionary statements: P243: Take precautionary measures against static discharge.
P273: Avoid release to the environment.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing.
Rinse skin with water.
P321: Specific treatment (see instructions on this label).
P370+378: In case of fire: Use carbon dioxide for extinction.

Label elements under CHIP:

Hazard symbols: Irritant.



Risk phrases: R10: Flammable.
R43: May cause sensitisation by skin contact.
R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R66: Repeated exposure may cause skin dryness or cracking.

Safety phrases: S2: Keep out of the reach of children.
S24: Avoid contact with skin.
S29: Do not empty into drains.
S37: Wear suitable gloves.

Precautionary phrases: Contains cobalt 6 (clp format), methyl ethyl ketoxime. May produce an allergic reaction.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

CALCIUM DRIER 4%

EINECS	CAS	CHIP Classification	CLP Classification	Percent
-	-	-: R10; N: R51/53; Xn: R65; -: R66	-	2.050%

[cont...]

SAFETY DATA SHEET

TEXTURED DECKING OIL

Page: 3

WHITE SPIRIT

265-185-4	64742-82-1	-: R10; N: R51/53; Xn: R65; -: R66; -: R66	-	0.196%
-----------	------------	---	---	--------

2-OCTYL-2H-ISOTHIAZOL-3-ONE

247-761-7	26530-20-1	Xn: R22; T: R23/24; C: R34; Sens.: R43; N: R50/53	Acute Tox. 3: H331; Acute Tox. 3: H311; Acute Tox. 4: H302; Skin Corr. 1B: H314; Skin Sens. 1: H317; Aquatic Chronic 1: H410; Aquatic Acute 1: H400	0.064%
-----------	------------	--	---	--------

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Transfer to hospital if there are burns or symptoms of poisoning.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Do not induce vomiting. Consult a doctor.

Inhalation: Move to fresh air in case of accidental inhalation of vapours. Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious and breathing is OK, place in the recovery position. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact. There may be redness or whiteness of the skin in the area of exposure.

Eye contact: There may be irritation and redness.

Ingestion: There may be vomiting and diarrhoea. Nausea and stomach pain may occur.

Inhalation: There may be shortness of breath with a burning sensation in the throat.

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Carbon dioxide (CO₂). Dry chemical powder. Alcohol resistant foam. Sand or earth. Do NOT use water jet.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In a fire, hazardous decomposition products such as smoke and Carbon Monoxide may be produced.

5.3. Advice for fire-fighters

Advice for fire-fighters: Exposure to decomposition products may be a hazard to health. Appropriate self-

[cont...]

SAFETY DATA SHEET

TEXTURED DECKING OIL

Page: 4

contained breathing apparatus may be required. Cool closed containers exposed to fire with water spray. Do NOT allow run-off from fire fighting to enter drains or water courses.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Ventilate the area. Eliminate all sources of ignition. No Smoking. Avoid inhaling vapour. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing (see section 8).

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. If the product enters drains or sewers, the local water company should be contacted immediately. In the case of contamination of streams, rivers or lakes contact the relevant environment agency.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Contain and collect spillages with non-combustible absorbent materials, e.g. sand, earth, vermiculite. Transfer into a suitable container for disposal in accordance with the waste regulations (see section 13) Do not use equipment in clean-up procedure which may produce sparks. Clean preferably with a detergent, avoid the use of solvents. There is a danger that absorbent material, used to clean up, may spontaneously combust. Absorbents should be sprayed with water prior to disposal.

6.4. Reference to other sections

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area. Avoid inhalation of vapour. Avoid skin and eye contact. Smoking, eating and drinking should be prohibited in areas of storage and use. Earth any equipment used in handling. Use non-sparking tools. Rags used to apply the oil may self-ignite without warning. Remove used cloths/rags from premises regularly and always at close of business. Rags should ideally be burnt. If this is not possible they should be washed in warm soapy water and disposed of without crumpling. Absorbents should be sprayed with water prior to disposal. The Manual Handling Operations Regulations may apply to the handling of containers of this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from direct sunlight. Exclude sources of heat, sparks and open flame. Take precautionary measures to prevent product spills into drains, the ground or waters. Although the storage of this product is not subject to specific statutory requirements, the principles

[cont...]

SAFETY DATA SHEET

TEXTURED DECKING OIL

Page: 5

contained in the HSE guidance note Storage of Flammable Liquids in containers, should be observed.

Suitable packaging: Ideally, keep in original container. If transfer is necessary use glass or coated steel containers.

7.3. Specific end use(s)

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

2-OCTYL-2H-ISOTHIAZOL-3-ONE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	0.05 mg/m ³	0.05 mg/m ³	-	-

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and/or solvent vapours below the relevant occupational exposure limits, suitable respiratory protective equipment should be worn (see Respiratory protection below).

Respiratory protection: All personal protective equipment, including respiratory protective equipment, used to control exposure to hazardous substances must be selected to meet the requirements of the COSHH Regulations.

Hand protection: Where repeated skin exposure may occur, wear PVC or Nitrile gloves.

Eye protection: Safety goggles. Ensure eye bath is to hand.

Skin protection: Overalls are normally suitable, PVC apron if risk of splashing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Clear and colour range

Odour: Paraffinic.

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Not miscible

Viscosity: Oily

Kinematic viscosity: 32

[cont...]

SAFETY DATA SHEET

TEXTURED DECKING OIL

Page: 6

Viscosity test method: Flow time in seconds in a 3 mm ISO cup (ISO 2431)

Flash point°C: 38

Relative density: 0.86 @ 20C

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Chemical stability: Stable under normal storage and handling conditions (see Section 7).

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Conditions to avoid: Avoid heat, flames and sparks. Direct sunlight.

10.5. Incompatible materials

Materials to avoid: Oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In a fire, hazardous decomposition products such as smoke and carbon monoxide may be produced.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

2-OCTYL-2H-ISOTHIAZOL-3-ONE

ORL	RAT	LD50	550	mg/kg
SKN	RBT	LD50	690	mg/kg

Relevant effects for mixture:

Effect	Route	Basis
Sensitisation	DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact. There may be redness or whiteness of the skin in the area of exposure.

Eye contact: There may be irritation and redness.

Ingestion: There may be vomiting and diarrhoea. Nausea and stomach pain may occur.

Inhalation: There may be shortness of breath with a burning sensation in the throat.

[cont...]

SAFETY DATA SHEET

TEXTURED DECKING OIL

Page: 7

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

12.3. Bioaccumulative potential

12.4. Mobility in soil

Mobility: Insoluble in water. Partially volatile. Partially absorbed into soil. The product should not be allowed to enter drains or water courses or be deposited where it can affect ground or surface waters.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: There is no data available on the product itself.

Section 13: Disposal considerations

13.1. Waste treatment methods

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1263

14.2. UN proper shipping name

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

[cont...]

SAFETY DATA SHEET

TEXTURED DECKING OIL

Page: 8

15.2. Chemical Safety Assessment

Chemical safety assessment: Safety Data Sheet complies with UK regulatory references in accordance with CHIP 3.1.

Section 16: Other information

Other information

Other information: DANGER of spontaneous combustion. After use, any cloths or rags should ideally be immediately burnt but if this is not possible, then they should be washed in warm soapy water.

Even after washing the rags must never be crumpled into a ball but spread out and disposed of. Use synthetic fibre cloths where possible as natural fibres, especially cotton, increase the chances of spontaneous combustion.

Brushes and rollers should be cleaned with White Spirit and then washed in warm soapy water.

Phrases used in s.2 and s.3: EUH208: Contains <name of sensitising substance>. May produce an allergic reaction.

H226: Flammable liquid and vapour.

H302: Harmful if swallowed.

H311: Toxic in contact with skin.

H314: Causes severe skin burns and eye damage.

H317: May cause an allergic skin reaction.

H331: Toxic if inhaled.

H410: Very toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

R10: Flammable.

R22: Harmful if swallowed.

R23/24: Toxic by inhalation and in contact with skin.

R34: Causes burns.

R43: May cause sensitisation by skin contact.

R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

Legend to abbreviations: PNEC = predicted no effect level

DNEL = derived no effect level

LD50 = median lethal dose

LC50 = median lethal concentration

[cont...]

SAFETY DATA SHEET

TEXTURED DECKING OIL

Page: 9

EC50 = median effective concentration

IC50 = median inhibitory concentration

dw = dry weight

bw = body weight

cc = closed cup

oc = open cup

MUS = mouse

GPG = guinea pig

RBT = rabbit

HAM = hamster

HMN = human

MAM = mammal

PGN = pigeon

IVN = intravenous

SCU = subcutaneous

SKN = skin

DRM = dermal

OCC = ocular/corneal

PCP = physico-chemical properties

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.