



# WOOD FINISHES DIRECT

The following Product Datasheet is provided by **Sadolin**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:  
[Sadolin Garden Furniture Oil](#)



## Garden Furniture Oil

**Sadolin Garden Furniture Oil** is an advanced formulation that enriches and enhances the appearance of all wooden garden furniture. By combining the highest quality oils with wax, **Sadolin Garden Furniture Oil** will keep your furniture as beautiful as the day you first bought it. The oils deeply penetrate into the wood enriching its natural beauty. The wax provides excellent water repellancy ensuring the wood is protected. A superior way to retain the natural colour of all garden furniture.

<b>Properties</b>	
<b>Composition</b>	Natural, drying / hardening oil
<b>Coating System</b>	New / bare timber: 2 – 3 coats, or more depending on the species of wood.
<b>Finish</b>	Clear, satin finish.
<b>Recommended Application Rate</b>	Up to 20m <sup>2</sup> per litre on smooth, planed timber. These figures are intended as a guide. The actual coverage will depend on a number of factors, including timber species, surface condition, moisture content, method of application and climatic conditions during application.
<b>Minimum Wet Film Thickness</b>	Not applicable
<b>Dry Film Thickness</b>	Not applicable
<b>Drying Time @20°C/65%RH</b>	Touch dry: 4-6 hours Recoatable: 16-24 hours <b>Note:</b> Drying times are dependent upon absorption, type of substrate and drying conditions. At low temperatures and / or conditions of high relative humidity, drying times will be extended.
<b>Volume Solids</b>	Approximately 50%
<b>VOC Content</b>	EU limit value for this product (cat. A/ e): 400 g/l (2010). This product contains max 399 g/l VOC.
<b>Flash Point</b>	61°C (closed cup)
<b>Colour Range</b>	Clear. As with all translucent coatings, the final colour and sheen are dependent on a number of factors, including the timber species, colour and cut, and the presence of any existing coating. A trial application is recommended prior to the commencement of work.
<b>Container Size</b>	
	<b>Sadolin Garden Furniture Oil</b> is available in 1 litre containers.
<b>General Information</b>	
	The following information is provided for guidance purposes, sample specifications for all Sadolin woodcare finishes are available on the Sadolin website, ( <a href="http://www.sadolin.co.uk">www.sadolin.co.uk</a> ). All products should be applied in accordance with the manufacturer's instructions, BS 6150: 2006 and BS 8000: Part 1: 1989. <b>Crown Paints</b> are unable to guarantee results as we have no control over the conditions under which products are applied.
<b>Preparation</b>	
<b>General</b>	Timber surfaces must be suitably prepared, clean, sound and dry. The moisture content should not exceed 18% prior to coating. Organic growths must be removed and infected surfaces should be treated with a suitable fungicidal solution. Remaining sound surfaces should be cleaned using a warm water and mild detergent and rinsed thoroughly with clean water. Resinous deposits should be removed with a scraper. Remove any remaining residues and degrease any exposed bare timber surface by wiping with a clean, lint free cloth, dampened with methylated spirits, frequently changing the face of the cloth. Allow solvent to fully evaporate before overcoating. "Knotting agents" should not be used with <b>Sadolin Garden Furniture Oil</b> . Fillers specifically designed for use with timber such as the Sadolin woodfillers should be used for making good any minor surface defects, imperfections and open joints etc. General or All Purpose fillers are not suitable. Only use non - ferrous screws, nails and fixings.  <b>Sadolin Garden Furniture Oil</b> should ideally be applied onto bare timber or previously oiled surfaces. Existing varnishes or paints must be completely removed. Never use steel wool or brushes with metallic bristles. Remove wax using a chemical stripper or sharp solvent.  Remove any stains with a damp cloth. If necessary, use a proprietary wooden floor cleaner to remove tougher stains. Ingrained dirt may be removed by gently using a fine nylon scouring pad dipped in <b>Sadolin Garden Furniture Oil</b> .
<b>New Timber</b>	Lightly abrade along the grain using a suitable abrasive paper taking care not to damage or scratch the timber surface. Remove all dust.

<b>Existing Coatings</b>	<b>Sadolin Garden Furniture Oil</b> is not suitable on surfaces which have been previously painted, varnished or waxed. In such cases, all previous treatments should be removed completely and the surfaces treated as 'New Timber'. Any grey denatured exposed timber surfaces must be thoroughly sanded back to clean, bright timber. Organic growths must be removed and infected surfaces should be treated with a suitable fungicidal solution. Remaining sound surfaces should be cleaned using a warm water and mild detergent and rinsed thoroughly with clean water and allowed to dry.
<b>Application</b>	
<b>Conditions</b>	Do not apply if there is a risk of rain, or when air / substrate temperatures are below 8°C or above 25°C, or if the relative humidity is above 80% during application or drying periods. Protect from frost and rain until dry. Failure to meet these requirements may adversely affect the drying, visual quality and durability of the finish.
<b>Initial Procedure</b>	<b>Sadolin Garden Furniture Oil</b> is supplied ready for use and should not be thinned. Shake can thoroughly before use. During use the Furniture Oil should be at ambient temperatures.
<b>Applying the Product</b>	For best results use a good quality, soft bristled brush or clean, lint free cloth. Apply in a full flowing coat in the direction of the grain, ensuring complete saturation of the timber. Avoid over spreading the Furniture Oil as this will reduce the protection afforded and may result in a poor quality finish. To avoid formation of 'glossy' patches, after 1 hour, any excess oil should be removed by wiping with a clean, lint free cloth.
<b>Maintenance</b>	Wipe off any spills immediately. After the initial treatment, a maintenance coat/treatment, once or twice a year (depending on the level of exposure) or when the surface looks dull, will be required. Regular maintenance will restore the lustre and should be carried out before bare wood is exposed.
<b>Cleaning Equipment</b>	Remove as much product as possible from tools before cleaning. Clean brushes and equipment with a proprietary brush cleaner immediately after use. If spilled, <b>Sadolin Garden Furniture Oil</b> should be removed immediately while still wet, using a warm detergent solution. <b>Caution</b> – Application rags and paper which have been wetted with the product may self-ignite without warning. Dispose of safely to avoid fire risk. Lay paper out flat to dry in single layers in a well-ventilated area and wash all rags out well in warm, soapy water before disposal.
<b>Storage</b>	Ensure this pack is stored upright and secure at all times. Crown Paints Limited cannot accept liability for damage caused by spillage. Do not store below 5°C or above 40°C.
<b>Relevant Standards</b>	
	.Not applicable.
<b>Health, Safety and the Environment</b>	
	<p>It is the policy of <b>Crown Paints</b> to provide the highest standard of safety, health and environmental advice and information. To this end, material safety data sheets covering every product are supplied to our customers and are freely available to users on request, by contacting us on the number given below. The safety phrases on the containers and material safety data sheets should be read before using this product.</p> <p><b>Removal of lead paint.</b> Take special precautions during the surface preparation of pre 1960's painted surfaces as they may contain harmful lead. Remove all such coating materials in accordance with the appropriate legislation. A guide on "How to remove old lead paint safely" is available via the British Coatings Federation Ltd. (Tel. 01372 360660).</p> <p><b>Surface Preparation and Applications.</b> Treatments such as sanding and burning off, etc. of paint films may generate hazardous dust and/or fumes. Work in well ventilated areas. Use suitable personal respiratory equipment together with any other Personal Protection Equipment (PPE) as necessary.</p> <p><b>Environment.</b> Crown Paints are committed to achieving the highest standards of health and safety at work and to minimising any impact our operations and products may have on the quality of the environment. We will provide such information as is necessary to customers to ensure so far as is reasonably practicable that our products can be used, transported, stored and disposed of safely without risk to health or the environment.</p> <p>It is recommended that any waste material be taken to a household waste disposal site provided by your Local Authority. Do not empty waste materials into drains, watercourses or access routes to septic tanks.</p> <p><b>Customer Service.</b> For help or more information contact our Customer Relations Team on 0330 0240 298. Before using this product please ensure you have the latest information.</p> <p><b>The above information is correct at the date of issue, April 2015.</b></p>