

The following Product Datasheet is provided by Starcke

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit: Starcke (Ersta) 15 Hole 150mm Aluminium Velcro Backed Sanding Discs

ERSTA



Product Information

Article No. 514 C2/N and 514 D/N Aluminium Oxide Paper

Base Stock	Flexible C- and robust D-weight latex paper, tear resistant	
Bonding	514 C2: Special resin with stearate top coat free of any contaminating substances affecting the blending of the lacquer.514 D: Special resin.	
Grain Type	Aluminium oxide	
Coating	Very open coat	
Grain Size	514 C2: P 800 - P 150 514 D: P 120 - P 60, P 40	
Manufactured Width	1650 mm	
Availability	Velcro discs, without and with holes for sanding machines with dust extraction, sheets, cut sheets, rolls and foam rolls.	
Market Segment	Automotive industry - vehicle manufacture and repair. Dry sanding of electrocoat, primer and subsequent paint finish.	
Advantages	 The dust-repellent additive incorporated as top coat prevents premature clogging of the grain surface. Unlike conventional stearate coating this repellent effect is maintained throughout the product life. Full resinoid bonding ensures excellent performance and durability. It is best suited for grinding new generation water based lacquers. High durability, low clogging of the grain surface because of a 21-hole disc system in our form 598. Best results will be achieved with the appropriate back-up pad also available from Starcke. 	
Car Metal Paint Shop	Wood Floor SandingPaint Lacquer FillerChina CeramicsLeatherGlassPlasticsStone	

STARCKE GmbH & Co. KG Markt 10 | 49324 Melle, Germany

Phone	+49 (0) 5422 966-0
Telefax	+49 (0) 5422 966-444
E-Mail	info@starcke.de
Internet	www.starcke.de