



WOOD FINISHES DIRECT

The following Technical Datasheet is provided by **Woca**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:
[Woca Antique Oak Lye](#)



Antique Oak Lye produces an ammonia-smoked appearance to oak wood. This product is user-friendly but corrosive and should be handled with caution during application. Since the product reacts with the tannic acid in the oak, the colour after application may vary depending on the concentration of tannin in the wood. However, it creates a very unique colour and vintage appearance. The final colour is achieved after 1-2 months.

- **Requires subsequent treatment with oil or soap**
- **Only for oak wood**
- **Does not contain pigments**



Application area

Used for priming of oak wood. Creates an ammonia-smoked look.

Work description

Preparation	The unfinished woodwork must be clean, dry and finely sanded (grit 100-120) before applying the lye. Always remember to test on a small area in order to check the surface and the compatibility of the product.
Treatment	Shake the container well and pour the lye into a plastic bucket. Apply an even coat of the lye with the WOCA Applicator, a nylon brush or roller lengthwise along the grain. Apply at least 1 L of lye per 10 m ² of wood. Leave wood to dry for approx. 2-4 hours at 20°C. Clean with WOCA Intensive Wood Cleaner and leave to dry for approx. 8-12 hours at 20°C. De-nib standing fibres with a medium e.g. green or bordeaux, sanding polishing pad. Remove the sanding dust with a vacuum cleaner. Finish the wood surface with a WOCA oil or soap.
Note	Depending on the amount of moisture and tannin in the oak, the colour may vary. Sapwood does not change to a dark colour.

Drying time

Drying time	2-4 hours.
-------------	------------



Antique Oak Lye

Gives oak an ammonia-smoked look

Technical Data Sheet

26.03.2020 – p. 2/2

Technical data

Binder	Sodium hydroxide, water.
Density	1-1,08
pH-value	13-14
Shelf life	3 years.
Coverage	8-10 m ² /L
Colours	Clear.
Cleaning of tools	Water.
Storage	+10-25°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer (max. +25°C).
Packaging	2.5 L
Authorisations	Certifikát IBR

Maintenance and related products

Related products	Intensive Wood Cleaner, #551525A
Accessories	WOCA Applicator, a nylon brush or roller Plastic bucket

Contact

WOCA Denmark A/S
Tvæervej 6
DK - 6640 Lunderskov
T +45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pre-treatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.