

The following Technical Datasheet is provided by Woca

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:
Woca Maintenance Box for Oiled Floors

Technical Data Sheet 26.03.2020 - p. 1/2

Intensive Wood Cleaner is a product that has been specially developed for the cleaning of all indoor wooden surfaces, such as furniture, floors, kitchen tables etc. and can be used on untreated, oiled or lacquered surfaces. Intensive Wood Cleaner is a priming cleaner, that can be used on particularly stubborn stains or before a surface is treated with for example oil, lacquer or soap.

- For unfinished, oiled, waxed, lacquered or soaped indoor wood surfaces
- Prepares surfaces for additional treatment
- Basic cleaning and grease removal
- High efficiency



Application area

Cleaning of new, untreated, sanded and treated wood. Ideal for all species of wood.

Work description

Preparation

Always remember to test on a less visible spot to check the compatibility of the surface with the product.

Treatment

Light treatment:

Mix Intensive Wood Cleaner and warm water. Se mixing ratio below. Wipe the wood surface with a well-wrung mop. Let the surface dry completely before subsequent treatment.

- Untreated, soap-treated or oiled surfaces: Mix 125 ml of Intensive Wood Cleaner with 2.5 L warm water.
- Lacquered or painted wood surfaces: Mix 125 ml. of Intensive Wood Cleaner with 2.5 L warm water.

Optimal result:

For best results, use two buckets: one with soap water and the second with clean water to rinse the dirty mop.

Untreated wood surfaces: 1] Use Intensive Wood Cleaner in the same way as for normal washing. 2] Wipe the wood surface with a well-wrung mop. If the surface is very dirty, repeat. 3] Let the surface dry completely before subsequent treatment.

Soap-treated and oiled wood surfaces: 1) Use Intensive Wood Cleaner in the same way as for normal washing and leave to work for 5 minutes before wiping down with clean water. Alternatively, use a hand-held pad or a machine, then dry any excess wood cleaner with a cloth or mop. For heavy soiling, repeat wash if necessary. 2) Let the surface dry completely before subsequent treatment. 3) Intensive Wood Cleaner leaves treated surfaces completely free of soap or oil, so they should be re-treated with Natural Soap or Diamond Oil Active.

Lacquered or painted wood surfaces: 1) Use Intensive Wood Cleaner in the same way as for normal washing. It is important to use a tightly wrung mop or cloth, in order not to leave a wet surface. Wipe down with a dry cloth afterwards if necessary. Repeat wash it necessary. 2) For re-treatment of lacquered floors, you should use Master Cleaner or Master Care.

Note

Use WOCA Wood Stain Remover for particularly stubborn stains.

Drying time

Drying time

2-8 hours at 20°C.



Technical data

Binder Water, tensides, complex binder, carbamide

Density 1.04 g/ml

pH-value 10.5

Shelf life 3 years

Application Temperature 15-30°C

200-300 m²/L Coverage

Colours Colourless

Mixing ratio 1:20-1:40, depending on the degree of soiling or surface.

+10-25°C. Keep out of reach of children. Do not expose Storage

to heat (e.g. sunlight). Store frost-free during winter and

cool during summer (max. +25°C).

Packaging 1 L - 2.5 L

Migration test of non-

desired materials

Authorisations

Indoor Climate Labelled

EN 71-3

IBR-certified

Maintenance and related products

Related products Natural Soap, #511010

Maintenance Oil, #527310

Maintenance Gel, #527802/527902

Master Cleaner, #684510 Master Care, #684110

Accessories Мор

Cloth

Contact

WOCA Denmark A/S

Tværvej 6

DK - 6640 Lunderskov T +45 9958 5600

info@wocadenmark.com wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.