

The following Technical Datasheet is provided by Woca

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit: Woca Natural Soap

Clean and maintain oiled, waxed and soaped wood surfaces with Natural Soap. This mild, penetrating soap removes dirt and helps prevent the wood from drying out and cracking. It leaves behind a microscopic, breathable soap layer on the surface that maximizes resistance and makes the surface easier to keep clean. Natural Soap is indoor climate labelled and free of perfume and additives.

- Nourishing effect
- · For the basic treatment of softwood
- Ideal for floors, furniture, table tops and panels
- · For regularly cleaning

| Α Ι | | |
|------|---------|------|
| Appi | ication | area |

For cleaning and maintenance of oiled, waxed and soaped wood surfaces.

Work description

Preparation Daily cleaning is made with vacuum cleaner or broom. The frequency of floor cleaning depends on the

wear on the floor. Very dirty floors may be cleaned with WOCA Intensive Wood Cleaner before using

Natural Soap.

Always remember to test on a less visible spot to check the compatibility of the surface with the

product.

Treatment

Natural Soap is shaken carefully before use. Make sure the pigments are mixed well. 125 ml Natural Soap

is mixed into 5 L of cold water. Wipe down the surface with a well-wrung mop.

For best results, use two buckets: one with soap water and the second with clean water to rinse the dirty mop. Clean the floor with minimum quantity of water – leave soap water on floor briefly in order to dissolve dirt. Remove dirty soap water with hard-wrung mop or cloth and rinse out in bucket with clean water. Always wipe down the surface with soap water and a hard-wrung mop or cloth in order to

re-establish the protective soap film.

Note Use mops/cloths with high cotton content. Don't use mops/cloths containing microfiber only.

Drying time

Technical data

Shelf life 3 years

Coverage 320-400 m²/L

Colours Natural, white and grey.

Mixing ratio 125 ml to 5 L water

Cleaning of tools With water and soap.

Storage +10-25°C. Keep out of reach of children. Do not expose

to heat (e.g. sunlight). Store frost-free during winter and

cool during summer (max. +25°C).

Packaging 1 L - 2.5 L - 5 L

Migration test of nondesired materials EN 71-3

acsirea materiais

Authorisations

Indoor Climate Labelled

IBR-certified

Maintenance and related products

Related products Intensive Wood Cleaner

Accessories Mop

Cloth

Contact

WOCA Denmark A/S

Tværvej 6

DK - 6640 Lunderskov T +45 9958 5600

info@wocadenmark.com wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.