

The following Technical Datasheet is provided by Woca

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit: <u>Woca Tannin Spot Remover</u>



Tannin Spot Remover Neutralises discolouration Technical Data Sheet 26.03.2020 - p. 1/2

Tannin Spot Remover effectively removes black spots caused by tannin/water reaction. May be used on unfinished, soaped, oiled or waxed interior surfaces.

- Ready mixed
- Simple application
- For small areas
- Requires additional treatment



Application area

May be used on unfinished, soaped, oiled or waxed interior surfaces.

Work description	
Preparation	Always remember to test on a small area in order to check the surface and the compatibility of the product.
Treatment	Spray Tannin Spot Remover evenly on the stain directly from the bottle. Leave the Tannin Spot Remover to dissolve the stain for 30-60 min. Wipe with cloth wrung in lukewarm water. Repeat operation if necessary. When the floor is completely dry, apply the original surface finish, e.g. oil, wax or soap to re-establish the protection of the surface.
Drying time	



Tannin Spot Remover Neutralises discolouration Technical Data Sheet 26.03.2020 - p. 2/2

Contact

Tværvej 6

WOCA Denmark A/S

DK - 6640 Lunderskov T +45 9958 5600

info@wocadenmark.com wocadenmark.com

This information is based on extensive laboratory testing and

Technical data

pH-value	2.1
Shelf life	3 years if unopened
Colours	Colourless
Cleaning of tools	With water and soap
Storage	Store safely, out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free.
Packaging	250 ml

Maintenance and related products

Related products

Accessories

Oil, wax or soap Cotton cloth practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.