



**WOOD  
FINISHES  
DIRECT**



Finish. Finished.

The following Safety Datasheet is provided by **Woodleys**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:  
[Woodleys Wax and Polish Remover](#)

# Woodleys

## Safety Data Sheet Woodleys Wax And Polish Remover

### 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY

#### 1.1. Product Identifier

Name	Woodleys Wax And Polish Remover
EC No.	919-446-0

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Use	Industrial Wood Coating
Name	Woodleys Wax And Polish Remover

#### 1.3. Details of the supplier of the safety data sheet

Company	Wood Finishes Direct LTD
Address	Unit B, 5 Acre Trade Estate, Park Farm Road, Folkestone, KENT, CT19 5DS
Web	www.wood-finishes-direct.com
Telephone	+44 (0)1303 213838
Fax	+44 (0)844 815 4992
Email	wood@finishes-direct.com
Email address of the competent person	wood@finishes-direct.com

#### 1.4. Emergency telephone number


Emergency telephone number	+44 (0)1303 213838
Company	Wood Finishes Direct LTD 7am - 7pm Mon - Fri, 8am - 5pm Sat, 10am - 4pm Sun.

### 2. HAZARDS IDENTIFICATION

#### 2.1. Classification of the substance or mixture

2.1.2. Classification - EC 1272/2008	Physical Flam. Liq. 3 - H226 Health EUH066;STOT Single 3 - H336;STOT Rep. 1 - H372;Asp. Tox. 1 - H304 Environmental Aquatic Chronic 2 - H411
Classification (1999/45)	Xn;R65. N;R51/53. R10, R66, R67.

#### 2.2. Label elements

EC No.	919-446-0
Contains:	low boiling point hydrogen treated naphtha
Hazard pictograms	

# Woodleys Wax And Polish Remover

## 2.2. Label elements

Signal Word	Danger
Hazard Statement	H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H336 May cause drowsiness or dizziness. H372 Causes damage to organs through prolonged or repeated exposure in contact with skin. H411 Toxic to aquatic life with long lasting effects.
Supplementary Precautionary Statements	P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ventilating/lighting/.../equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P260 Do not breathe dust/fume/gas/mist/vapours/spray. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P264 Wash ... thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area. P273 Avoid release to the environment. P280 Wear protective gloves/protective clothing/eye protection/face protection. P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. P304+340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P312 Call a POISON CENTER or doctor/physician if you feel unwell. P314 Get medical advice/attention if you feel unwell. P331 Do NOT induce vomiting. P370+378 In case of fire: Use ... for extinction. P391 Collect spillage. P403+233 Store in a well-ventilated place. Keep container tightly closed. P403+235 Store in a well-ventilated place. Keep cool. P405 Store locked up. P501 Dispose of contents/container to ...
Supplementary Label Information	EUH066 Repeated exposure may cause skin dryness or cracking.

## 2.3. Other Hazards

This product does not contain any PBT or vPvB Substances.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1. Classification of the substance or mixture

Low Boiling Point Hydrogen Treated Naptha		60 -100%
CAS-No.: 64742-82-1	EC No.: 265-185-4	
Classification (EC 1272/2008)	Classification (67/548)	
Flam. Liq. 3 - H226	Xn;R65.	
EUH066	N;R51/53.	
STOT Single 3 - H336	R10,R66,R67.	
Asp. Tox. 1 - H304		
Aquatic Chronic 2 - H411		

REACH Registration Number 01-2119458049-33-xxxx

EC No. 919-446-0

Revision 2  
Revision date 03/12/2015

Page 2 of 8  
Print Date 14/02/2017

# Woodleys Wax And Polish Remover

## 4. FIRST AID MEASURES

### 4.1. Description of first aid measures

General Information	Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.
Inhalation	Move the exposed person to fresh air at once. Get medical attention. Provide rest, warmth and fresh air. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Do Not use mouth to mouth ventilation
Eye contact	Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.
Skin contact	Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention promptly if symptoms occur after washing.
Ingestion	DO NOT INDUCE VOMITING! NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Drink plenty of water. Get medical attention immediately! Provide rest, warmth and fresh air.

### 4.2. Most important symptoms and effects, both acute and delayed

Inhalation	Vapours may cause headache, fatigue, dizziness and nausea. Difficulty in breathing.
Eye contact	Vapour, spray or dust may cause chronic eye irritation or eye damage.
Skin contact	Prolonged contact may cause redness, irritation and dry skin.
Ingestion	Central nervous system depression. Nausea, vomiting.

### 4.3. Indication of any immediate medical attention and special treatment needed

Inhalation	Seek medical attention
Eye contact	Seek medical attention
Skin contact	Seek medical attention.
Ingestion	Seek medical attention.

## 5. FIREFIGHTING MEASURES

### 5.1. Extinguishing media

Suitable Extinguishing Media	Extinguish with alcohol-resistant foam, carbon dioxide or dry powder.
Suitable Extinguishing Media	Do not use water jet as an extinguisher, as this will spread the fire.

### 5.2. Special hazards arising from the substance or mixture

Hazardous Combustion Products	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.
Unusual Fire & Explosion Hazards	Vapours are heavier than air and may spread near ground to sources of ignition.
Specific Hazards	The product is flammable, and heating may generate vapours which may form explosive vapour/air mixtures.

### 5.3. Advice for firefighters

Special Fire Fighting Procedures	Avoid breathing fire vapours. Cool containers exposed to flames with water until well after the fire is out. Keep run-off water out of sewers and water sources. Dike for water control.
Protective Measures In Fire	Self contained breathing apparatus and full protective clothing must be worn.

# Woodleys Wax And Polish Remover

## 6. ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

Take precautionary measures against static discharges. Ensure suitable personal protection (including respiratory protection) during removal of spillages in a confined area. Do not smoke, use open fire or other sources of ignition.

### 6.2. Environmental precautions

Avoid discharge into drains, water courses or onto the ground. Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

### 6.3. Methods and material for containment and cleaning up

Wear necessary protective equipment. Absorb in vermiculite, dry sand or earth and place into containers. Collect in containers and seal securely. Remove containers and flush area with water.

### 6.4. Reference to other sections

## 7. HANDLING AND STORAGE

Storage Class

### 7.1. Precautions for safe handling

Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site. Avoid inhalation of vapours/spray and contact with skin and eyes.

### 7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container. Ground container and transfer equipment to eliminate static electric sparks. Flammable/combustible - Keep away from oxidisers, heat and flames.

Storage Class

Flammable liquid storage.

### 7.3. Specific end use(s)

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

Ingredient Comments

WEL = Workplace Exposure Limits DNEL = Derived No Effect Level

DNEL Industry Dermal 44 mg/kg/day

DNEL Industry Inhalation. 330 mg/kg/day

### 8.2. Exposure controls



8.2.1. Appropriate engineering controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

Eye / face protection

Wear approved safety goggles.

Skin protection - Handprotection

Use protective gloves.

Skin protection - Other

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

## Woodleys Wax And Polish Remover

Respiratory protection	No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit. Use respiratory equipment with gas filter, type A2.
Hygiene Measures	DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly with soap & water if skin becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1. Information on basic physical and chemical properties

Appearance	Clear Liquid
Colour	Colourless to pale yellow
Odour	Pungent
Odour threshold	No data available
pH	No data available
Melting point	No data available
Initial boiling point	135-220
Flash point	39 °C
Evaporation rate	0.13 (EtEt=1)
Flammability (solid, gas)	No data available
Vapour pressure	<2.7 kPa 20c
Vapour density	>1
Relative density	.774 to 0.79 15c
Partition coefficient	No data available
Autoignition temperature	No data available
Viscosity	No data available
Explosive properties	No data available
Oxidising properties	No data available
Solubility	Immiscible in water

#### 9.2. Other information

VOC	780 g/l
-----	---------

### 10. STABILITY AND REACTIVITY

#### 10.1. Reactivity

	There are no known reactivity hazards associated with this product.
--	---

#### 10.2. Chemical stability

	Stable under normal temperature conditions and recommended use.
--	---

#### 10.3. Possibility of hazardous reactions

	Not determined.
--	-----------------

#### 10.4. Conditions to avoid

	Avoid contact with acids and oxidising substances. Avoid heat, flames and other sources of ignition. Avoid exposure to high temperatures or direct sunlight. Avoid excessive heat for prolonged periods of time.
--	--

#### 10.5. Incompatible materials

Materials To Avoid	Strong oxidising substances.
--------------------	------------------------------

#### 10.6. Hazardous decomposition products

Fire creates	Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO <sub>2</sub> ). Carbon.
--------------	--

# Woodleys Wax And Polish Remover

## 11. TOXICOLOGICAL INFORMATION

### 11.1.4. Toxicological Information

Acute Toxicity (Oral LD50)	> 15000 mg/kg Rat
Acute Toxicity (Dermal LD50)	> 3400 mg/kg Rabbit
Acute Toxicity (Inhalation LC50)	13.1 mg/l (vapours) Rat
Inhalation	In high concentrations, vapours are anaesthetic and may cause headache, fatigue, dizziness and central nervous system effects.
Ingestion	Liquid irritates mucous membranes and may cause abdominal pain if swallowed. Swallowing concentrated chemical may cause severe internal injury. Harmful: may cause lung damage if swallowed.
Skin Contact	Acts as a defatting agent on skin. May cause cracking of skin, and eczema. Prolonged or repeated exposure may cause severe irritation.
Eye Contact	May cause severe irritation to eyes.
Target Organs	Skin Eyes Respiratory system, lungs.
Specific Effects	May cause damage to the kidneys.

## 12. ECOLOGICAL INFORMATION

Ecotoxicity	The product contains a substance which is toxic to aquatic organisms and which may cause long term adverse effects in the aquatic environment.
-------------	--

### 12.1. Toxicity

	LC 50, 96 Hrs, Fish mg/l 10-30 mg/l EC 50, 48 Hrs, Daphnia, mg/l 10-22 mg/l IC 50, 72 Hrs, Algae, mg/l 4.6-10 mg/l
--	--

### 12.2. Persistence and degradability

Degradability	The product is expected to be biodegradable.
---------------	--

### 12.3. Bioaccumulative potential

	No data is available on this product.
--	---------------------------------------

### 12.4. Mobility in soil

	The product is insoluble in water and will spread on the water surface.
--	---

### 12.5. Results of PBT and vPvB assessment

	This product does not contain any PBT or vPvB Substances.
--	---

### 12.6. Other adverse effects

	Not determined.
--	-----------------

## 13. DISPOSAL CONSIDERATIONS

General Information	When handling waste, consideration should be made to the safety precautions applying to handling of the product.
---------------------	--

### 13.1. Waste treatment methods

	Dispose of as special waste in compliance with local and national regulations.
--	--

## 14. TRANSPORT INFORMATION

### Hazard pictograms



#### 14.1. UN number

UN1300

#### 14.2. UN proper shipping name

TURPENTINE SUBSTITUTE (White Spirit)

#### 14.3. Transport hazard class(es)

ADR/RID/ADN	3
ADR/RID/ADN Class	Class 3: Flammable liquids.
ADR Label No.	3

#### 14.4. Packing group

III

#### 14.5. Environmental hazards

Environmental hazards	Yes
Marine pollutant	Yes

#### 14.6. Special precautions for user

Emergency Action Code	3Y
Hazard No. (ADR)	30
Tunnel Restriction Code	(D/E)

#### IMDG

EMS Code	F-E S-E
----------	---------

#### 14.6. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Cat Y

## 15. REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Uk Regulatory References	The Control of Substances Hazardous to Health Regulations 2002 (S.I 2002 No. 2677) with amendments.
Statutory Instruments	The Classification, Labelling and Packaging of substances and mixtures Regulations EC 1272/2008 (CLP) and amendments.
Approved Code Of Practice	Classification and Labelling of Substances and Preparations Dangerous for Supply.
Guidance Notes	Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108).

### 15.2. Chemical safety assessment



# Woodleys Wax And Polish Remover

## 16. OTHER INFORMATION

### Other information

Risk Phrases In Full	Revision Date 03/12/2015 Revision 2 Supersedes Date 26/01/2012
	R10 Flammable. R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R65 Harmful: may cause lung damage if swallowed. R66 Repeated exposure may cause skin dryness or cracking. R67 Vapours may cause drowsiness and dizziness.
Hazard Statements In Full	EUH066 Repeated exposure may cause skin dryness or cracking. H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects.
<b>General information</b>	
	This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy