



WOOD FINISHES DIRECT

The following Product Datasheet is provided by **Liberon**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:
[Liberon Pure Tung Oil](#)



Pure Tung Oil

- Premium, pure and natural oil for wood care
- Ideal for use on food contact surfaces – kitchen worktops, chopping boards and salad bowls
- Provides a long lasting matt finish
- Water, heat and alcohol resistant
- Suitable for interior and exterior use
- Recommended for use on external oak



USAGE

Interior and exterior

COVERAGE

1 Litre

10-12 m²

APPLICATION

Brush or cloth

DRYING TIME

24 hours between coats, 4 days final

TOOL CLEANING

White Spirit

Product use

Liberon Pure Tung Oil is highly resistant to water, alcohol and food acids. Providing a hard wearing finish it is ideal for surfaces such as kitchen worktops, tables and all high quality interior wood. Pure Tung Oil, with no added dryers, is a natural, non-toxic product which can be used on toys and objects in contact with food such as salad bowls etc. Being a penetrating oil it allows the wood to age gracefully and develop a natural patina. Recommended for use on exterior oak.

Preparation

Ensure the wood surface is bare: remove any wax finishes with Liberon Wax and Polish Remover and any varnish finishes with Liberon Fine Wood Stripper. Clean, dry and ensure the surface is dust free.

Application

Apply Tung Oil using a brush or lint-free cotton cloth. For ease of application dilute the first one or two coats with up to 50% white spirit. Allow the oil to penetrate for 20 to 30 minutes then wipe off the excess oil using a clean lint-free cloth. Allow to dry for 24 hours between coats.

Apply further coats of Tung Oil as above, reducing the amount of white spirit used with subsequent coats. Again allow 24 hours to dry.

Apply the last one or two coats of Tung Oil undiluted, as in previous applications. After the final coat has been applied and excess removed leave for 24 hours and wipe over again to aid drying and remove any oil that may have surfaced. We recommend a minimum of 4 coats; more coats will be required for porous or external surfaces. For best results gently rub with Liberon Ultra Fine Steel Wool (0000) between coats.

Leave for a few days before use to allow the Pure Tung Oil to dry fully. Furniture items may be finished with Liberon Wax Polish Black Bison for an improved lustre.

Important: Oil finishes bring out the natural colours of timber. A wet surface will be an indication of the final colour. Always test product on a spare surface or inconspicuous area for colour, compatibility and end result.

Cleaning and maintenance

Pure Tung Oil must be maintained on a regular basis. Apply at least once or twice a year or more if required, depending upon exposure to the weather and usage. On exposed external timbers it is important to apply sufficient coats of oil to give the initial protection.

**Precautions**

- Tung Oil is extracted from nuts and may cause an allergic reaction.
- Store Liberon Tung Oil at a temperature above 5 °C. Always replace the lid otherwise the oil can deteriorate.
- Oily cloths can self combust. Do not leave impregnated cloths in bundles. Before discarding lay them flat outside to dry to avoid a fire hazard.
- If the excess is not removed and the surface becomes sticky, wipe with white spirit to remove the sticky film and allow to dry before continuing.

Packaging

Pure Tung Oil is available in 250ml, 500ml, 1L and 5L containers.