



WOOD FINISHES DIRECT

The following Technical Datasheet is provided by **Liberon**

Wood Finishes Direct cannot be held liable for the information contained within this document.

For purchasing information visit:
[Liberon Superior Protection Woodstain](#)



SUPERIOR PROTECTION WOODSTAIN



750ml – 2.5L

- *Tough & durable weather protection*
 - *Quick-drying*
 - *Water-repellent & UV-resistant*
- *Designed for all exterior & interior vertical woodwork*

Liberon Superior Protection Woodstain is specially designed to protect and decorate outdoor woods exposed to bad weather conditions and UV. Its microporous formulation allows the wood to breathe.

PREPARATION

The wood to be stained must be clean, dry, in good condition and not greasy. Sand corners and edges to round them slightly.

- **Bare or refurbished wood:** Sand with sandpaper to obtain a smooth surface and remove dust. Apply a suitable wood treatment product.
- **Exotic woods, oak, chestnut:** Dilute the 1st coat with 10% water and apply a second non-diluted coat. On greasy woods, degrease the surface with acetone.
- **Stained woods:** Brush to remove any loose or flaking finishes. Use sandpaper to obtain a smooth surface and remove dust.

APPLICATION

Ideal application conditions are between 12° and 25°C, in dry, wind-free weather.

- Stir the product well before and during use using a wide stirrer.
- Apply in 2 coats. For a spray application, dilute with 10% water.

Remove as much of the woodstain as possible from the tools after use. Do not dispose of residues and washing water/solvents in the sink, toilet, sewer, bin, etc., in order to avoid discharge into the environment.

THE SECRET OF LIBERON

- Do not apply to thermo-heated, thermo-treated or acidic woods.
- For bright colours on new or exposed woods, it may be necessary to apply a 3rd coat.
- The clear shade is recommended only for maintenance on previously stained and tinted woods or to dilute other colour shades.
- Results may vary according to wood species. Always test product on a small or inconspicuous area for colour, compatibility and end result.







SUPERIOR PROTECTION WOODSTAIN



750ml – 2.5L

- Tough & durable weather protection
 - Quick-drying
 - Water-repellent & UV-resistant
- Designed for all exterior & interior vertical woodwork

Liberon Superior Protection Woodstain is specially designed to protect and decorate outdoor woods exposed to bad weather conditions and UV. Its microporous formulation allows the wood to breathe.



Drying time:
recoat



Drying time:
fully dry



Tool cleaning:
water



Tools:
brush, roller,
spray gun

2.5l
±30^{sqm}

The 8-year guarantee applies for:

- New wood or renovation of common species when product is applied according to preparation and application instructions.
- **EXPOSURE:** Only vertical surfaces. For South and South-West exposure, apply 3 coats.
- The guarantee is limited to refunding of the product (presentation of the receipt and the tin) and concerns only the appearance of the woodstain.

This product should be used in accordance with the manufacturer's instructions. Recommendations are for guidance only since conditions of use are completely beyond our control. For technical or practical information on this or other Liberon products please contact Liberon Technical Services on 01797 367555.

This notice is intended to provide information. The information is based on our current knowledge and experience based on conditions of use that comply with the standards or DTU in force. Given the multiplicity of factors that can influence the use of our products, they cannot exempt the user from his own experiences. No legal warranty can be derived from our information. This data sheet supersedes all previous editions.